

## Button

by Piero Lissoni , 2004



Indoor and outdoor wall/ceiling lamp providing diffused light. Slightly opaline (PC opal), injection-molded polycarbonate diffuser. Closure screw/diffuser support in die-cast and handpolished aluminum alloy protected with liquid transparent paint. The wall attachment is slightly, injection-molded polycarbonate. The light bulb support is 30% glass fiberreinforced nylon, injection molded and matte white. Silicone elastomer dust and waterproof seals.





Mounting	Ceiling and wall
Environment	Indoor, Outdoor
Weight	2.1 Kg
Light sources available	1 x 22W 2GX13 T5 FSC 1800lm warm white [e] cod. RF11177 + 1 x 40W 2GX13 T5 FSC 3400lm warm white [e] cod. RF11178

Emergency	Without
Voltage	220-240V
Power	22W + 40W
Battery	No
Supply included	Yes

Materials	Polycarbonate
-----------	---------------

Colors	F3180009 - White/Transparent
--------	------------------------------

Certificate	   
-------------	--




## Button HL

by Piero Lissoni , 2004



Wall/ceiling fixture providing diffused lighting for indoor use. Hand-blown opal ply glass diffuser (transparent – opal – transparent) with acid finish. Sheared, deep-drawn steel sheet wall/ceiling attachment with white galvanized finish. Sheared, deep-drawn steel sheet reflector painted white for high temperatures. Closing cover in injection molded tecnopolymer with chrome finish. Satin-finish incandescent line voltage halogen lamps.



Mounting	Ceiling and wall
Environment	Indoor
Weight	13.5 Kg
Light sources available	5 x LED 3W G9 290lm 2700K [e] cod. 28425 Non dimmable 5 x LED 2W G9 240lm 2700K cod. RF26520 [e] No Dimmable
Emergency	Without
Switching	Luminosity can be adjusted by means of traditional dimmers installed in the recessed versions.
Voltage	220-250V
Power	5x MAX 40W
Battery	No
Supply included	Yes
Materials	Glass
Colors	 F3190009 - White
Certificate	