





DIRO SBL S IP 927 W

11436 9200 W

AVAILABLE IN

BLACK 11436 9200 B

WHITE 11436 9200 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 121
RECESSED DEPTH (MM)	80
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 350mA-DC INCL.PC SBL

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED FLEX 5,9W / CRI>90 / 2700K / 900lm
LED TECHNICS (LIGHT SOURCE)	900 lm // 5,9 W // 153 lm/W
LED TECHNICS (LUMINAIRE)	338lm // 6,8W // 50lm/W

For detailed installation instructions, please consult the manual: [11436_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-



Notes:



DIRO SBL M 927 W

202 296 92 W

AVAILABLE IN
BLACK 202 296 92 B
WHITE 202 296 92 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 156
RECESSED DEPTH (MM)	70
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 350mA-DC INCL.PC SBL

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED FLEX 9,8W / CRI>90 / 2700K / 1500lm
LED TECHNICS (LIGHT SOURCE)	1500 lm // 9,8 W // 153 lm/W
LED TECHNICS (LUMINAIRE)	761lm // 11,3W // 68lm/W

For detailed installation instructions, please consult the manual: [202_296_XX_HAND.pdf](#)

DIRO SBL M 927 W
 202 296 92 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-

Notes:





DIRO SBL L 927 B

11437 9200 B

AVAILABLE IN

BLACK 11437 9200 B

WHITE 11437 9200 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 208
RECESSED DEPTH (MM)	70
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	non adjustable
INFORMATION	INCL.LED POWER SUPPLY 1050mA-DC INCL.PC SBL

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 18,5W / CRI>90 (R9: 50) / 2700K / 2281lm
LED TECHNICS (LIGHT SOURCE)	2281lm // 18,1 W // 126 lm/W
LED TECHNICS (LUMINAIRE)	1463lm // 20,8W // 70lm/W

For detailed installation instructions, please consult the manual: [11437_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-

Notes: