


Fountain Ring 12x 2 Watt Mono

PROLED®



The PROLED FOUNTAIN RING is conceived for underwater illumination of fountains and water gardens.

- dimmable or DMX 512, DALI, 1-10 V controllable by MBNLED MULTI power supplies or MBNLED PRO CONTROLLER MULTI

This IP68 luminaire can not be operated out of water for over 15 minutes (cooling).

TECHNICAL DATA

IP classification:	IP68 (for underwater use max. 1 m)
Power source:	24 VDC
Housing:	stainless steel 316, 10 mm tempered glass
Electrical connection:	1x cable 3 m H05RN-F 2x 1,0 mm ² with 2-PIN IP68 connector male
Operating temperature range:	-10° C till +40° C

PHOTOMETRIC DATA

LED type:	OSRAM 2 Watt high power
Luminous flux:	white 1900 Lumen warm white 1500 Lumen
Colour temperature:	white 6500 K warm white 3000 K
CRI:	white 70 warm white 80
Beam angle:	25°

Due to conditions of production photometric data can vary from production batch to production batch within the EU directive.

PRODUCT TYPES

order code	colour	LED pcs	LED power	power consumption*	weight	EEI
L1344	white	12	24 Watt	30 Watt	2,8 kg	A
L1346	warm white	12	24 Watt	30 Watt	2,8 kg	A

*Actual power consumption