


Model Sheet




Finish	18 Graphite ADAPTA RF 9913 WX
LED temperature color	3000 K
Dimming	Sensor
Installation type	Surface Canopy
Materials	Profile: Aluminum Diffuser: Borosilicate glass
Light source	1 x LED STRIP 24V 10W G
LED	CRI>90 871.2 lm 87.12 3000 K
Driver	CV - Constant Voltage 100-240 V 50/60 HZ
Remarks	The glass is made of borosilicate. It is typical for the glass to have small air bubbles, some inclusions and tiny scratches. These do not affect the quality or the resistance of the glass.
	☐ ☒ Dimmer ☒ LED ☒ IP20 ☒ Bi-volt ☒ Dry Location ☒ 50-60Hz

Application	Wall Lamps
Packaging	1 Box 0.76 m x 0.76 m x 0.27 m Gross weight 11.6 Net weight 4 Vol. 0.1559

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.




Photometric Data

Efficiency	1
Coordinate System	CG
Total Flux	445.29 lm
Maximum Value	188.65 cd/klm

Other Applications



Model Sheet



Finish 18 Graphite
ADAPTA RF 9913 WX

LED temperature color 3000 K

Dimming Sensor

Installation type Surface Canopy

Materials Profile: Aluminum
Diffuser: Borosilicate glass

Light source 1 x LED STRIP 24V 17,2W
G

LED CRI>90 1504.8 lm 87.12
3000 K

Driver CV - Constant Voltage
100-240 V 50/60 HZ

Remarks The glass is made of borosilicate. It is typical for the glass to have small air bubbles, some inclusions and tiny scratches. These do not affect the quality or the resistance of the glass.

☐ ☒ **Dimmer** **LED**
IP20 **Bi-volt** **Dry Location** **50-60Hz**


Application Wall Lamps

Packaging 1 Box
1.12 m x 1.12 m x 0.345 m
Gross weight 24.8
Net weight 11.5
Vol. 0.4327

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Efficiency 1
Coordinate System CG
Total Flux 897.91 lm
Maximum Value 188.65 cd/klm

Other Applications

