





Ø200



IC F1 Outdoor H 1350 mm Brushed Stainless Steel/Occhio di Pernice

F012A04C005 - Brushed Stainless Steel/Occhio di Pernice

Floor lamp with diffused light for exterior use.

Structure in painted brushed stainless steel or brushed brass; marble base in various colours. Available in four standard combinations: black/black lava painted steel, deep brown/travertino imperiale, satinized brass/grey lava, satinized stainless steel/occhio di pernice.

The structural parts are chemically treated for protection against atmospheric elements.

Opalescent blown glass diffuser.

5-m cable with IP44 Schuko plug suitable for outdoor use.

Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30–100%.


Main specifications

Lamp categoryLED retrofitMountingsFloorEnvironmentOutdoor

Optical

Lighting type Light distribution Optical type

Direct Symmetric Diffused light



Luminous flux luminaire 700 lm

Beam Angle:		0°
<u>h(m)</u>	E(l x)	D(m)
1	57	
2	14	
3	6	
4	4	
5	0	

Electrical

Frequency (Hz) 50-60 Emergency Without Voltage (V) 220-240 Insulation class II Dimmable

Driver remote included
Driver type Dimmer on
board

Physical

Color Brushed

Stainless Steel/Occhio di Pernice

Orientation Fixed Weight (kg) 5

Note

Bulb not included. LED: max 8W - E14

IC F1 Outdoor H 1350 mm Brushed Stainless Steel/Occhio di Pernice





LED 8W E14 800lm 3000K [e] Dimmable LED 8W E14 700lm 2700K [e] Dimmable RF26565

RF26767







Ø300



IC F2 Outdoor H 1852 mm Brushed Stainless Steel/Occhio di Pernice

F012B04C005 - Brushed Stainless Steel/Occhio di Pernice

Floor lamp with diffused light for exterior use.

Structure in painted brushed stainless steel or brushed brass; marble base in various colours. Available in four standard combinations: black/black lava painted steel, deep brown/travertino imperiale, satinized brass/grey lava, satinized stainless steel/occhio di pernice.

The structural parts are chemically treated for protection against atmospheric elements.

Opalescent blown glass diffuser.

5-m cable with IP44 Schuko plug suitable for outdoor use.


Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30–100%.

Main specifications

Lamp categoryLED retrofitPower (W)30MountingsFloorEnvironmentOutdoor

Optical

Lighting type Light distribution Optical type Direct Symmetric Diffused light



Luminous flux luminaire 1400 lm

Beam Angle:		0
h(m)	E(lx)	D(m
1	86	
2	21	
3	10	
4	5	

0

5

Electrical

Frequency (Hz) 50-60 Emergency Without Voltage (V) 220-240 Insulation class II Dimmable Yes
Driver remote included

Dimmer on board

Physical

Driver type

Color Brushed

Stainless Steel/Occhio di Pernice Fixed

Orientation Fixed Weight (kg) 10

Note

Bulb not included. LED: max 15W - E27

IC F2 Outdoor H 1852 mm Brushed Stainless Steel/Occhio di Pernice





LED 15W E27 2000lm 3000K [e] Dimmable RF28666 LED 15W E27 2000lm 2700K [e] Dimmable RF28665

IC F1 Outdoor

F012A04C005		IC F1 Outdoor H 1350 mm Brushed Stainless Steel/Occhio di Pernice LED retrofit
F012A03C059		IC F1 Outdoor H 1350 mm Brass Finish/Grey Lava LED retrofit
F012A02C037		IC F1 Outdoor H 1350 mm Burgundy Red/Black Lava LED retrofit
F012A02C030		IC F1 Outdoor H 1350 mm Black/Black Lava LED retrofit
F012A01C018	186	IC F1 Outdoor H 1350 mm Deep Brown/Travertino Imperiale LED retrofit
IC F2 Outdoor		
F012B04C005		IC F2 Outdoor H 1852 mm Brushed Stainless Steel/Occhio di Pernice LED retrofit
F012B03C059		IC F2 Outdoor H 1852 mm Brass Finish/Grey Lava LED retrofit
F012B02C037		IC F2 Outdoor H 1852 mm Burgundy Red/Black Lava LED retrofit
F012B02C030	e _c v	IC F2 Outdoor H 1852 mm Black/Black Lava LED retrofit
F012B01C018	1	IC F2 Outdoor H 1852 mm Deep Brown/Travertino Imperiale LED retrofit