RA8 DIXIT 27K S/DRIVER MAX12W IP44 26° BI

Code: 238-250CN-21

Fixed downlight for accent lighting, designed for the last generation of COB LEDs. LED drivers should be ordered separately, the wattage of the fittings changes depending on the selected driver. Protection rating IP44. Low glare level: UGR < 19.

General specifications

Designer	**Ivela Design Team**
Installation environment	**Interior**
Native mounting type	**Rebated flush-mounted**
Mounting type	**Rebated flush-mounted**
Ideal application locations	**Residential** **Hospitality** **Showroom** **Museum** **Office** **Commercial space**
Packaging	**Box**
Wire incandescent test	**850**
Made in	**Italy**

Physical specifications

Shape	**Round**
Body material	**Aluminum**
Body finish	**Matte**
Body color	**White**
Frontal material	**Aluminum**
Frontal finish	**Matte**
Frontal color	**White**
Thermal dissipation	**Passive**
Covering with insulating materials	**No**
IP	**IP43**
Waterstop	**No**

Salt mist resistance	**No**

Lighting specifications

Luminous luminaire (lm)	**1538**
Power / Consumption (W)	**12**
W source	**12**
Light type	**White**
Color Temperature	**2700K**
CRI	**80**
Life time	**L80B10**

Optical specifications

Light beam distribution	**Symmetric**
Emission angle α (°)	**26**
Optics type	**Mirror metallized thermoplastic reflector**
Optical diffuser finish	**Metallized**
Optical diffuser material	**Termoplastic**
Orientability	**Fixed**

Electrical specifications

Power supply availability	**Not included**
Power supply position	**Remote**
Dimmable	**Yes**
Power supply type	**Current**
Insulation class	**III**

Dimensions and weight

Height / Thickness (mm)	**74**
Diameter (mm)	**80**
Recessed hole width (mm)	**70**
Recess depth (mm)	**74**

General conditions

Warranty	**5 years**

Via B. Buozzi 15 - 20050 Liscate (Milano)
Tel. +39 02 9500121 - info@ivela.it - **www.ivela.it**