
DELTALIGHT




LUNELLE 52 SPM20 92730 MDL

REFERENCE 32820 9220 BRA

AVAILABLE IN
BRUSHED ALU 32820 9220 BRA
BRUSHED ALU-BLACK 32820 9220 BRA-B
BRUSHED ALU-WHITE 32820 9220 BRA-W
BRUSHED ANTHRACITE 32820 9220 BRAT
BRUSHED ANTHRACITE-BLACK 32820 9220 BRAT-B
BRUSHED ANTHRACITE-WHITE 32820 9220 BRAT-W
BRUSHED BROWN BRONZE 32820 9220 BRBB
BRUSHED BROWN BRONZE BLACK 32820 9220 BRBB-B
BRUSHED BROWN BRONZE WHITE 32820 9220 BRBB-W
BRUSHED COPPER 32820 9220 BRCU
BRUSHED COPPER-BLACK 32820 9220 BRCU-B
BRUSHED COPPER-WHITE 32820 9220 BRCU-W
BRUSHED GOLD 32820 9220 BRG
BRUSHED GOLD-BLACK 32820 9220 BRG-B
BRUSHED GOLD-WHITE 32820 9220 BRG-W
BRUSHED OLD BRONZE 32820 9220 BROB
BRUSHED OLD BRONZE-BLACK 32820 9220 BROB-B
BRUSHED OLD BRONZE-WHITE 32820 9220 BROB-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED 5,6W / CRI>90 (R9: 80) / 2700K / 485lm
SDCM	SDCM3
RISKGROUP	RG2
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	485lm // 5,6W // 86lm/W
LED TECHNICS (LUMINAIRE)	388lm // 6,4W // 60lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

Accessories

VISOR 52

DELTALIGHT

LUNELLE 52 SPM20 92730 MDL

32820 9220 BRA

For detailed installation instructions, please consult the manual : **32820_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

Light altering devices



32810 0010 DC VISOR 52 DC ☐

Notes:


DELTALIGHT




LUNELLE 52 SPM20 92730 DIM5

REFERENCE 32821 9225 BRA

AVAILABLE IN
BRUSHED ALU 32821 9225 BRA
BRUSHED ALU-BLACK 32821 9225 BRA-B
BRUSHED ALU-WHITE 32821 9225 BRA-W
BRUSHED ANTHRACITE 32821 9225 BRAT
BRUSHED ANTHRACITE-BLACK 32821 9225 BRAT-B
BRUSHED ANTHRACITE-WHITE 32821 9225 BRAT-W
BRUSHED BROWN BRONZE 32821 9225 BRBB
BRUSHED BROWN BRONZE BLACK 32821 9225 BRBB-B
BRUSHED BROWN BRONZE WHITE 32821 9225 BRBB-W
BRUSHED COPPER 32821 9225 BRCU
BRUSHED COPPER-BLACK 32821 9225 BRCU-B
BRUSHED COPPER-WHITE 32821 9225 BRCU-W
BRUSHED GOLD 32821 9225 BRG
BRUSHED GOLD-BLACK 32821 9225 BRG-B
BRUSHED GOLD-WHITE 32821 9225 BRG-W
BRUSHED OLD BRONZE 32821 9225 BROB
BRUSHED OLD BRONZE-BLACK 32821 9225 BROB-B
BRUSHED OLD BRONZE-WHITE 32821 9225 BROB-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED 5,6W / CRI>90 (R9: 80) / 2700K / 485lm
SDCM	SDCM3
RISKGROUP	RG2
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	485lm // 5,6W // 86lm/W
LED TECHNICS (LUMINAIRE)	388lm // 6,4W // 60lm/W

Requirements

LED POWER SUPPLY 48V-DC

Accessories

VISOR 52

DELTALIGHT

LUNELLE 52 SPM20 92730 DIM5

32821 9225 BRA

For detailed installation instructions, please consult the manual : **32821_XXX5_HAND.pdf**

FINISH YOUR SPECIFICATION

Light altering devices



32810 0010 DC VISOR 52 DC ☐

Notes:


DELTALIGHT




LUNELLE 52 M26L 92730 MDL

REFERENCE 32822 9220 BRA-B

AVAILABLE IN
BRUSHED ALU-BLACK 32822 9220 BRA-B
BRUSHED ALU-WHITE 32822 9220 BRA-W
BRUSHED ANTHRACITE-BLACK 32822 9220 BRAT-B
BRUSHED ANTHRACITE-WHITE 32822 9220 BRAT-W
BRUSHED BROWN BRONZE BLACK 32822 9220 BRBB-B
BRUSHED BROWN BRONZE WHITE 32822 9220 BRBB-W
BRUSHED COPPER-BLACK 32822 9220 BRCU-B
BRUSHED COPPER-WHITE 32822 9220 BRCU-W
BRUSHED GOLD-BLACK 32822 9220 BRG-B
BRUSHED GOLD-WHITE 32822 9220 BRG-W
BRUSHED OLD BRONZE-BLACK 32822 9220 BROB-B
BRUSHED OLD BRONZE-WHITE 32822 9220 BROB-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED 5,6W / CRI>90 (R9: 80) / 2700K / 485lm
SDCM	SDCM3
RISKGROUP	RG2
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	485lm // 5,6W // 86lm/W
LED TECHNICS (LUMINAIRE)	388lm // 6,4W // 60lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

Accessories

VISOR 52

DELTALIGHT

LUNELLE 52 M26L 92730 MDL

32822 9220 BRA-B

For detailed installation instructions, please consult the manual : **32822_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

Light altering devices



32810 0010 DC VISOR 52 DC ☐


Notes:


DELTALIGHT

LUNELLE 52 M26L 92730 DIM5

REFERENCE 32823 9225 BRA-B

AVAILABLE IN
BRUSHED ALU-BLACK 32823 9225 BRA-B
BRUSHED ALU-WHITE 32823 9225 BRA-W
BRUSHED ANTHRACITE-BLACK 32823 9225 BRAT-B
BRUSHED ANTHRACITE-WHITE 32823 9225 BRAT-W
BRUSHED BROWN BRONZE BLACK 32823 9225 BRBB-B
BRUSHED BROWN BRONZE WHITE 32823 9225 BRBB-W
BRUSHED COPPER-BLACK 32823 9225 BRCU-B
BRUSHED COPPER-WHITE 32823 9225 BRCU-W
BRUSHED GOLD-BLACK 32823 9225 BRG-B
BRUSHED GOLD-WHITE 32823 9225 BRG-W
BRUSHED OLD BRONZE-BLACK 32823 9225 BROB-B
BRUSHED OLD BRONZE-WHITE 32823 9225 BROB-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED 5,6W / CRI>90 (R9: 80) / 2700K / 485lm
SDCM	SDCM3
RISKGROUP	RG2
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	485lm // 5,6W // 86lm/W
LED TECHNICS (LUMINAIRE)	388lm // 6,4W // 60lm/W

Requirements

LED POWER SUPPLY 48V-DC

Accessories

VISOR 52

For detailed installation instructions, please consult the manual : **32823_XXX5_HAND.pdf**


DELTALIGHT

LUNELLE 52 M26L 92730 DIM5

32823 9225 BRA-B

FINISH YOUR SPECIFICATION

Light altering devices



32810 0010 DC VISOR 52 DC ☐

Notes: