
DELTALIGHT




LUNELLE 52 ON 92730

REFERENCE 32813 9220 BRA

AVAILABLE IN
BRUSHED ALU 32813 9220 BRA
BRUSHED ANTHRACITE 32813 9220 BRAT
BRUSHED BROWN BRONZE 32813 9220 BRBB
BRUSHED COPPER 32813 9220 BRCU
BRUSHED GOLD 32813 9220 BRG
BRUSHED OLD BRONZE 32813 9220 BROB





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED 5,6W / CRI>90 (R9: 80) / 2700K / 485lm
SDCM	SDCM3
RISKGROUP	RG2
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	485lm // 5,6W // 86lm/W
LED TECHNICS (LUMINAIRE)	388lm // 6,4W // 60lm/W

Requirements

LED POWER SUPPLY 500mA-DC

Accessories

VISOR 52

For detailed installation instructions, please consult the manual : **32813_XXX0_HAND.pdf**

DELTALIGHT

LUNELLE 52 ON 92730

32813 9220 BRA


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 1 -> 6 (6) ☐

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 82



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 — 1 -> 4 (2) ☐

Dimtype: DALI


Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 — 1 -> 10 (7) ☐

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 — 1 -> 3 (2) ☐

Dimtype: 1-10V or push button


Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 — 1 -> 3 (2) ☐

Dimtype: DALI


Cutout dimension (mm): 55



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL — 1 -> 4 ☐

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 1 -> 3 ☐

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48



21012 0595 LED POWER SUPPLY 500mA-DC 10W DIM5 — 1 -> 1 ☐

Dimtype: DALI


Cutout dimension (mm): 35

DELTALIGHT

LUNELLE 52 ON 92730

32813 9220 BRA

Light altering devices



32810 0010 DC VISOR 52 DC

Notes:


DELTALIGHT




LUNELLE 52 ON 2 48V 92730 MDL

REFERENCE 32814 9220 BRA-B

AVAILABLE IN
BRUSHED ALU-BLACK 32814 9220 BRA-B
BRUSHED ANTHRACITE-BLACK 32814 9220 BRAT-B
BRUSHED BROWN BRONZE BLACK 32814 9220 BRBB-B
BRUSHED COPPER-BLACK 32814 9220 BRCU-B
BRUSHED GOLD-BLACK 32814 9220 BRG-B
BRUSHED OLD BRONZE-BLACK 32814 9220 BROB-B





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED 5,6W / CRI>90 (R9: 80) / 2700K / 485lm
SDCM	SDCM3
RISKGROUP	RG2
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	485lm // 5,6W // 86lm/W
LED TECHNICS (LUMINAIRE)	388lm // 6,4W // 60lm/W

Requirements

LED POWER SUPPLY 48V DC

Options

DIMMABLE MODULATOR

Accessories

VISOR 52

For detailed installation instructions, please consult the manual : **32814_XXX0_HAND.pdf**


DELTALIGHT

LUNELLE 52 ON 2 48V 92730 MDL

32814 9220 BRA-B


FINISH YOUR SPECIFICATION

SMART 48



300 90 011 SMART 48 MODULATOR DIM9


Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

Dimtype: WDL = wireless dimmable

LED power supplies



21032 0390 LED POWER SUPPLY 48V-DC / 90W

Dimtype: non-dimmable

Cutout dimension (mm): 75



21032 0600 LED POWER SUPPLY 48V-DC / 35W

Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices



32810 0010 DC VISOR 52 DC

Notes:


DELTALIGHT




LUNELLE 52 TRIMLESS 92730

REFERENCE 32811 9220 BRA

AVAILABLE IN
BRUSHED ALU 32811 9220 BRA
BRUSHED ANTHRACITE 32811 9220 BRAT
BRUSHED BROWN BRONZE 32811 9220 BRBB
BRUSHED COPPER 32811 9220 BRCU
BRUSHED GOLD 32811 9220 BRG
BRUSHED OLD BRONZE 32811 9220 BROB





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Semi-recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø kit
RECESSED DEPTH (MM)	80
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED 5,6W / CRI>90 (R9: 80) / 2700K / 485lm
SDCM	SDCM3
RISKGROUP	RG2
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	485lm // 5,6W // 86lm/W
LED TECHNICS (LUMINAIRE)	388lm // 6,4W // 60lm/W

Requirements

MOUNTING KIT R53 TRIMLESS
LED POWER SUPPLY 500mA-DC

Accessories

VISOR 52

For detailed installation instructions, please consult the manual : **32811_XXX0_HAND.pdf**

DELTALIGHT

LUNELLE 52 TRIMLESS 92730

32811 9220 BRA

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **Plasterboard**	32210 0050 - MOUNTING KIT R53 TRIMLESS O.F.A.	Required
 **Concrete + plaster**	32210 0050 - MOUNTING KIT R53 TRIMLESS O.F.A.	Required
 **Lintel + plaster**	32210 0050 - MOUNTING KIT R53 TRIMLESS O.F.A.	Required
 **Hollow-core slab + plaster**	32210 0050 - MOUNTING KIT R53 TRIMLESS O.F.A.	Required


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 1 -> 6 (6) ☐

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 82



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 — 1 -> 4 (2) ☐

Dimtype: DALI


Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 — 1 -> 10 (7) ☐

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 — 1 -> 3 (2) ☐

Dimtype: 1-10V or push button

Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 — 1 -> 3 (2) ☐


Dimtype: DALI

Cutout dimension (mm): 55

DELTALIGHT

LUNELLE 52 TRIMLESS 92730


32811 9220 BRA



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL — 1 -> 4

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 1 -> 3

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48




21012 0595 LED POWER SUPPLY 500mA-DC 10W DIM5 — 1 -> 1

Dimtype: DALI

Cutout dimension (mm): 35

Mounting kits



32210 0050 MOUNTING KIT R53 TRIMLESS O.F.A.

Cutout dimension (mm): 82

Light altering devices



32810 0010 DC VISOR 52 DC

Notes:


DELTALIGHT




LUNELLE 52 CLIP 92730

REFERENCE 32812 9220 BRA

AVAILABLE IN
BRUSHED ALU 32812 9220 BRA
BRUSHED ANTHRACITE 32812 9220 BRAT
BRUSHED BROWN BRONZE 32812 9220 BRBB
BRUSHED COPPER 32812 9220 BRCU
BRUSHED GOLD 32812 9220 BRG
BRUSHED OLD BRONZE 32812 9220 BROB





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Semi-recessed
CUTOUT SHAPE/SIZE (MM)	round - 40
RECESSED DEPTH (MM)	40
THICKNESS OF MOUNTING SURFACE (MM)	12
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED 5,6W / CRI>90 (R9: 80) / 2700K / 485lm
SDCM	SDCM3
RISKGROUP	RG2
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	485lm // 5,6W // 86lm/W
LED TECHNICS (LUMINAIRE)	388lm // 6,4W // 60lm/W

Requirements

LED POWER SUPPLY 500mA-DC

Accessories

VISOR 52

For detailed installation instructions, please consult the manual : **32812_XXX0_HAND.pdf**

DELTALIGHT

LUNELLE 52 CLIP 92730

32812 9220 BRA

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 — 1 -> 6 (6) ☐

Dimtype: 1-10V or DALI or push button

Cutout dimension (mm): 82



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 — 1 -> 4 (2) ☐


Dimtype: DALI

Cutout dimension (mm): 72

DELTALIGHT

LUNELLE 52 CLIP 92730


32812 9220 BRA



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 — 1 -> 10 (7) ☐

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 84



300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 — 1 -> 3 (2) ☐

Dimtype: 1-10V or push button


Cutout dimension (mm): 55



300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 — 1 -> 3 (2) ☐

Dimtype: DALI


Cutout dimension (mm): 55



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL — 1 -> 4 ☐

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 54



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 1 -> 3 ☐

Dimtype: mains (phase cut-off)

Cutout dimension (mm): 48



21012 0595 LED POWER SUPPLY 500mA-DC 10W DIM5 — 1 -> 1 ☐

Dimtype: DALI

Cutout dimension (mm): 35

Light altering devices



32810 0010 DC VISOR 52 DC ☐

Notes: