
DELTALIGHT




MONTUR MINI M 927

232 012 92 FBRX

AVAILABLE IN
ALU GREY 232 012 92 A
BLACK 232 012 92 B
FLEMISH BRONZE OUTDOOR 232 012 92 FBRX
ANTHRACITE 232 012 92 N
WHITE 232 012 92 W





View on website

General info	
LOCATION	indoor-outdoor
INSTALLATION	Ceiling Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	1.2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.GLASS OPAL INCL.LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 4,2W / CRI>90 (R9: 50) / 2700K / 584lm
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	584lm // 4,2W // 139lm/W
LED TECHNICS (LUMINAIRE)	239lm // 4,8W // 50lm/W

For detailed installation instructions, please consult the manual : **232_012_XX_HAND.pdf**

DELTALIGHT

MONTUR MINI M 927

232 012 92 FBRX

Notes: