



MONTUR S LED 927 FBRX

232 112 92 FBRX

AVAILABLE IN



ALU GREY 232 112 92 A

BLACK 232 112 92 B

FLEMISH BRONZE OUTDOOR 232 112 92 FBRX

ANTHRACITE 232 112 92 N

WHITE 232 112 92 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Ceiling Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	2.3
ADJUSTABILITY	non adjustable
INFORMATION	INCL.GLASS OPAL INCL.LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 6,3W / CRI>90 (R9: 50) / 2700K / 877lm
TM-30 VALUES	Rf: 93 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	877lm // 6,3W // 139lm/W
LED TECHNICS (LUMINAIRE)	526lm // 7,2W // 73lm/W

For detailed installation instructions, please consult the manual: [232_112_XX_HAND.pdf](#)



MONTUR S LED 927 FBRX

232 112 92 FBRX

Notes: