




Noctambule Suspension 1 Low Cylinder Bowl

■ F0263000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.



Main specifications

Mounting	Suspension	Lamp holder	LED Module, COB LED
Environment	Indoor dry location	Dimmable	Yes
Light source type	LED	Autoprotected Lamp	No
Light source replaceable	Replaceable (LED only) light source by a professional	Source Power (W)	36
		System Flux (lm)	1007
LED type	LED Module		

Optical

Lighting Type	Total
Lighting distribution	Symmetric
CCT (K)	2700
CRI>	90
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I	Dimmable type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Frequency (Hz)	50/60	Batteries Inside	No
Main Voltage (Vac)	120-277	Dimming Interface	Switch Integrated (Remote Dimmable)
Driver	Integrated	Power supply replaceable	Replaceable control gear by a professional
Dimmable	Yes	Cord length (mm)	4000
Charging Min Time	No		

Physical

Colour	Black
Net weight (kg)	10.7
Gross weight (kg)	23.59
IP	20
IP external	20





Noctambule Suspension 1 Low Cylinder Cone

■ F0268000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.



Main specifications

Mounting	Suspension	Lamp holder	LED Module, COB LED
Environment	Indoor dry location	Dimmable	Yes
Light source type	LED	Autoprotected Lamp	No
Light source replaceable	Replaceable (LED only) light source by a professional	Source Power (W)	36
		System Flux (lm)	973
LED type	LED Module		

Optical

Lighting Type	Total
Lighting distribution	Symmetric
CCT (K)	2700
CRI>	90
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I	Dimmable type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Frequency (Hz)	50/60	Batteries Inside	No
Main Voltage (Vac)	120-277	Dimming Interface	Remote Dimmable (Dimmer Not Included)
Driver	Integrated	Power supply replaceable	Replaceable control gear by a professional
Dimmable	Yes	Cord length (mm)	4000

Charging Min Time No

Physical

Colour	Black
Net weight (kg)	10.2
Gross weight (kg)	22.49
IP	20
IP external	20






Noctambule Suspension 2 Low Cylinder Bowl

■ F0273000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.



Main specifications

Mounting Environment	Suspension Indoor dry location	Lamp holder	LED Module, COB LED
Light source type	LED	Dimmable	Yes
Light source replaceable	Replaceable (LED only) light source by a professional	Autoprotected Lamp	No
LED type	LED Module	Number of heads	4
System Flux (lm)	1007	Source Power (W)	45

Optical

Lighting Type	Total
Lighting distribution	Symmetric
CCT (K)	2700
CRI>	90
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I	Dimmable type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Frequency (Hz)	50/60	Batteries Inside	No
Main Voltage (Vac)	120-277	Dimming Interface	Remote Dimmable (Dimmer Not Included)
Driver	Integrated	Power supply replaceable	Replaceable control gear by a professional
Dimmable	Yes	Cord length (mm)	4000
Charging Min Time	No		

Physical

Colour	Black
Net weight (kg)	14.2
Gross weight (kg)	31.31
IP	20
IP external	20






Noctambule Suspension 2 Low Cylinder Cone

■ F0270000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.



Main specifications

Mounting Environment	Suspension Indoor dry location	Lamp holder	LED Module, COB LED
Light source type	LED	Dimmable	Yes
Light source replaceable	Replaceable (LED only) light source by a professional	Autoprotected Lamp Source Power (W)	No 45
		System Flux (lm)	1259
LED type	LED Module		

Optical

Lighting Type	Total
Lighting distribution	Symmetric
CCT (K)	2700
CRI>	90
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I	Dimmable type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Frequency (Hz)	50/60	Batteries Inside	No
Main Voltage (Vac)	120-277	Dimming Interface	Remote Dimmable (Dimmer Not Included)
Driver	Integrated	Power supply replaceable	Replaceable control gear by a professional
Dimmable	Yes	Cord length (mm)	4000

Charging Min Time No

Physical

Colour	Black
Net weight (kg)	13.7
Gross weight (kg)	30.21
IP	20
IP external	20






Noctambule Suspension 3 High Cylinder

■ F0264000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.



Main specifications

Mounting Environment	Suspension Indoor dry location	Lamp holder Dimmable	LED Module Yes
Light source type	LED	Autoprotected Lamp	No
Light source replaceable	Replaceable (LED only) light source by a professional	Number of heads	4
LED type	LED Module	Source Power (W)	36
System Flux (lm)	1202		

Optical

Lighting Type	Total
Lighting distribution	Symmetric
CCT (K)	2700
CRI>	90
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I	Dimmable type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Frequency (Hz)	50/60	Batteries Inside	No
Main Voltage (Vac)	120-277	Dimming Interface	Remote Dimmable (Dimmer Not Included)
Driver	Integrated	Power supply replaceable	Replaceable control gear by a professional
Dimmable	Yes	Cord length (mm)	4000
Charging Min Time	No		

Physical

Colour	Black
Net weight (kg)	14.9
Gross weight (kg)	32.85
IP	20
IP external	20






Noctambule Suspension 3 Low Cylinder Bowl

■ F0274000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.



Main specifications

Mounting	Suspension	Lamp holder	LED Module, COB LED
Environment	Indoor dry location	Dimmable	Yes
Light source type	LED	Autoprotected Lamp	No
Light source replaceable	Replaceable (LED only) light source by a professional	Source Power (W)	54
	LED type	System Flux (lm)	1293

Optical

Lighting Type	Total
Lighting distribution	Symmetric
CCT (K)	2700
CRI>	90
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I	Dimmable type	Dimmable 0- 10V, Dimmable Push, Dimmable 1- 10V, Dimmable DALI 1
Frequency (Hz)	50/60	Batteries Inside	No
Main Voltage (Vac)	120-277	Dimming Interface	Remote Dimmable (Dimmer Not Included)
Driver	Integrated	Power supply replaceable	Replaceable control gear by a professional
Dimmable	Yes	Cord length (mm)	4000

Charging Min Time No

Physical

Colour	Black
Net weight (kg)	17.7
Gross weight (kg)	39.03
IP	20
IP external	20






Noctambule Suspension 3 Low Cylinder Cone

■ F0271000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.



Main specifications

Mounting Environment	Suspension Indoor dry location	Lamp holder	LED Module, COB LED
Light source type	LED	Dimmable	Yes
Light source replaceable	Replaceable (LED only) light source by a professional	Autoprotected Lamp Source Power (W)	No 54
		System Flux (lm)	1545
LED type	LED Module		

Optical

Lighting Type	Total
Lighting distribution	Symmetric
CCT (K)	2700
CRI>	90
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I	Dimmable type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Frequency (Hz)	50/60	Batteries Inside	No
Main Voltage (Vac)	120-277	Dimming Interface	Remote Dimmable (Dimmer Not Included)
Driver	Integrated	Power supply replaceable	Replaceable control gear by a professional
Dimmable	Yes	Cord length (mm)	4000

Charging Min Time No

Physical

Colour	Black
Net weight (kg)	17.2
Gross weight (kg)	37.93
IP	20
IP external	20






Noctambule Suspension 3 Low Cylinder

■ F0276000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.



Main specifications

Mounting	Suspension	Lamp holder	LED Module
Environment	Indoor dry location	Dimmable	Yes
Light source type	LED	Autoprotected Lamp	No
Light source replaceable	Replaceable (LED only) light source by a professional	Source Power (W)	36
		System Flux (lm)	1196
LED type	LED Module		

Optical

Lighting Type	Total
Lighting distribution	Symmetric
CCT (K)	2700
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I	Dimmable type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Frequency (Hz)	50/60	Batteries Inside	No
Main Voltage (Vac)	120-277	Dimming Interface	Remote Dimmable (Dimmer Not Included)
Driver	Integrated	Power supply replaceable	Replaceable control gear by a professional
Dimmable	Yes	Cord length (mm)	4000

Charging Min Time No

Physical

Colour	Black
Net weight (kg)	13.4
Gross weight (kg)	29.55
IP	20
IP external	20






Noctambule Suspension 4 High Cylinder

■ F0280000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.



Main specifications

Mounting	Suspension	Lamp holder	LED Module
Environment	Indoor dry location	Dimmable	Yes
Light source type	LED	Autoprotected Lamp	No
Light source replaceable	Replaceable (LED only) light source by a professional	Source Power (W)	45
		System Flux (lm)	1500
LED type	LED Module		

Optical

Lighting Type	Total
Lighting distribution	Symmetric
CCT (K)	2700
Cold Beam Lighting	No
Extreme Cut off	No

Electrical


Insulation class	I	Dimmable type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Frequency (Hz)	50/60	Batteries Inside	No
Main Voltage (Vac)	120-277	Dimming Interface	Remote Dimmable (Dimmer Not Included)
Driver	Integrated	Power supply replaceable	Replaceable control gear by a professional
Dimmable	Yes	Cord length (mm)	4000

Charging Min Time No

Physical

Colour	Black
Net weight (kg)	18.9
Gross weight (kg)	41.67
IP	20
IP external	20





Noctambule Suspension 4 Low Cylinder Bowl

■ F0275000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.

Main specifications

Mounting Environment	Suspension Indoor dry location	Lamp holder	LED Module, COB LED
Light source type	LED	Dimmable	Yes
Light source replaceable	Replaceable (LED only) light source by a professional	Autoprotected Lamp Source Power (W)	No 63
		System Flux (lm)	1579
LED type	LED Module		

Optical

Lighting Type	Total
Lighting distribution	Symmetric
CCT (K)	2700
CRI>	90
Cold Beam Lighting	No
Extreme Cut off	No

Electrical


Insulation class	I	Dimmable type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Frequency (Hz)	50/60	Batteries Inside	No
Main Voltage (Vac)	120-277	Dimming Interface	Remote Dimmable (Dimmer Not Included)
Driver	Integrated	Power supply replaceable	Replaceable control gear by a professional
Dimmable	Yes	Cord length (mm)	4000

Charging Min Time No

Physical

Colour	Black
Net weight (kg)	21.2
Gross weight (kg)	46.75
IP	20
IP external	20





Noctambule Suspension 4 Low Cylinder Cone

■ F0272000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.

Main specifications

Mounting Environment	Suspension Indoor dry location	Lamp holder	LED Module, COB LED
Light source type	LED	Dimmable	Yes
Light source replaceable	Replaceable (LED only) light source by a professional	Autoprotected Lamp Source Power (W)	No 63
		System Flux (lm)	1831
LED type	LED Module		

Optical

Lighting Type	Total
Lighting distribution	Symmetric
CCT (K)	2700
CRI>	90
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I	Dimmable type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Frequency (Hz)	50/60	Batteries Inside	No
Main Voltage (Vac)	120-277	Dimming Interface	Remote Dimmable (Dimmer Not Included)
Driver	Integrated	Power supply replaceable	Replaceable control gear by a professional
Dimmable	Yes	Cord length (mm)	4000

Charging Min Time No

Physical

Colour	Black
Net weight (kg)	20.7
Gross weight (kg)	45.64
IP	20
IP external	20






Noctambule Suspension 4 Low Cylinder

■ F0277000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.



Main specifications

Mounting	Suspension	Lamp holder	LED Module
Environment	Indoor dry location	Dimmable	Yes
Light source type	LED	Autoprotected Lamp	No
Light source replaceable	Replaceable (LED only) light source by a professional	Source Power (W)	45
		System Flux (lm)	1482
LED type	LED Module		

Optical

Lighting Type	Total
Lighting distribution	Symmetric
CCT (K)	2700
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I	Dimmable type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Frequency (Hz)	50/60	Batteries Inside	No
Main Voltage (Vac)	120-277	Dimming Interface	Remote Dimmable (Dimmer Not Included)
Driver	Integrated	Power supply replaceable	Replaceable control gear by a professional
Dimmable	Yes	Cord length (mm)	4000

Charging Min Time No

Physical

Colour	Black
Net weight (kg)	16.9
Gross weight (kg)	37.26
IP	20
IP external	20






Noctambule Suspension 5 High Cylinder

■ F0281000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.



Main specifications

Mounting	Suspension	Lamp holder	LED Module
Environment	Indoor dry location	Dimmable	Yes
Light source type	LED	Autoprotected Lamp	No
Light source replaceable	Replaceable (LED only) light source by a professional	Source Power (W)	54
		System Flux (lm)	1798
LED type	LED Module		

Optical

Lighting Type	Total
Lighting distribution	Symmetric
CCT (K)	2700
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I	Dimmable type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Frequency (Hz)	50/60	Batteries Inside	No
Main Voltage (Vac)	120-277	Dimming Interface	Remote Dimmable (Dimmer Not Included)
Driver	Integrated	Power supply replaceable	Replaceable control gear by a professional
Dimmable	Yes	Cord length (mm)	4000

Charging Min Time No

Physical

Colour	Black
Net weight (kg)	22.9
Gross weight (kg)	50.49
IP	20
IP external	20






Noctambule Suspension 5 Low Cylinder

■ F0278000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.



Main specifications

Mounting	Suspension	Lamp holder	LED Module
Environment	Indoor dry location	Dimmable	Yes
Light source type	LED	Autoprotected Lamp	No
Light source replaceable	Replaceable (LED only) light source by a professional	Number of heads	6
LED type	LED Module	Source Power (W)	54
System Flux (lm)	1768		

Optical

Lighting Type	Total
Lighting distribution	Symmetric
CCT (K)	2700
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I	Dimmable type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Frequency (Hz)	50/60	Batteries Inside	No
Main Voltage (Vac)	120-277	Dimming Interface	Remote Dimmable (Dimmer Not Included)
Driver	Integrated	Power supply replaceable	Replaceable control gear by a professional
Dimmable	Yes	Cord length (mm)	4000
Charging Min Time	No		

Physical

Colour	Black
Net weight (kg)	20.4
Gross weight (kg)	44.98
IP	20
IP external	20






Noctambule Suspension 6 High Cylinder

■ F0282000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.



Main specifications

Mounting	Suspension	Lamp holder	LED Module
Environment	Indoor dry location	Dimmable	Yes
Light source type	LED	Autoprotected Lamp	No
Light source replaceable	Replaceable (LED only) light source by a professional	Source Power (W)	63
		System Flux (lm)	2096
LED type	LED Module		

Optical

Lighting Type	Total
Lighting distribution	Symmetric
CCT (K)	2700
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I	Dimmable type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Frequency (Hz)	50/60	Batteries Inside	No
Main Voltage (Vac)	120-277	Dimming Interface	Remote Dimmable (Dimmer Not Included)
Driver	Integrated	Power supply replaceable	Replaceable control gear by a professional
Dimmable	Yes	Cord length (mm)	4000

Charging Min Time No

Physical

Colour	Black
Net weight (kg)	26.9
Gross weight (kg)	59.31
IP	20
IP external	20






Noctambule Suspension 6 Low Cylinder

■ F0279000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.



Main specifications

Mounting	Suspension	Lamp holder	LED Module
Environment	Indoor dry location	Dimmable	Yes
Light source type	LED	Autoprotected Lamp	No
Light source replaceable	Replaceable (LED only) light source by a professional	Source Power (W)	63
		System Flux (lm)	2054
LED type	LED Module		

Optical

Lighting Type	Total
Lighting distribution	Symmetric
CCT (K)	2700
Cold Beam Lighting	No
Extreme Cut off	No

Electrical

Insulation class	I	Dimmable type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Frequency (Hz)	50/60	Batteries Inside	No
Main Voltage (Vac)	120-277	Dimming Interface	Remote Dimmable (Dimmer Not Included)
Driver	Integrated	Power supply replaceable	Replaceable control gear by a professional
Dimmable	Yes	Cord length (mm)	4000

Charging Min Time No

Physical

Colour	Black
Net weight (kg)	23.9
Gross weight (kg)	52.7
IP	20
IP external	20

