



General info


DECORATIVO - Hanging

Indoor suspended lamp with integrated LED sources and diffuse light emission

Ean	8021696253671
Item	OZ SP D60 ON-OFF BIANCO
Installation	Suspension
Guarantee	5 years
Gross weight	2.69 kg
Volume	0.06762 m ³

Technical info

Net weight	1.63 kg
Insulation class	I
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	No dimmerable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included YES (by qualified operators only), electronic



Source info

Integrated source	Integrated LED module
Replaceable source	NO
Power	LED 47W
Emission	Diffuse
Max consumption	max 47 W
Features LED	LED SMD
CCT	3000 K
Duration LED (t. 25°C)	30000 h
CRI	> 80
Light beam	120°
Light beam flux	5000 lm
Useful light flux	2680 lm
Standby power	< 0.50



General info


DECORATIVO - Hanging

Indoor suspended lamp with integrated LED sources and diffuse light emission

Ean	8021696269436
Item	OZ SP D60 ON-OFF NERO
Installation	Suspension
Guarantee	5 years
Gross weight	2.69 kg
Volume	0.06762 m ³


Technical info

Net weight	1.63 kg
Insulation class	I
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	No dimmerable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included YES (by qualified operators only), electronic



Source info

Integrated source	Integrated LED module
Replaceable source	NO
Power	LED 47W
Emission	Diffuse
Max consumption	max 47 W
Features LED	LED SMD
CCT	3000 K
Duration LED (t. 25°C)	30000 h
CRI	> 80
Light beam	120°
Light beam flux	5000 lm
Useful light flux	2680 lm
Standby power	< 0.50



General info

DECORATIVO - Hanging

Indoor suspended lamp with integrated LED sources and diffuse light emission

Ean	8021696269443
Item	OZ SP D60 ON-OFF OTTONE
Installation	Suspension
Guarantee	5 years
Gross weight	2.69 kg
Volume	0.06762 m ³

Technical info

Net weight	1.63 kg
Insulation class	I
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	No dimmerable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included YES (by qualified operators only), electronic

Source info

Integrated source	Integrated LED module
Replaceable source	NO
Power	LED 47W
Emission	Diffuse
Max consumption	max 47 W
Features LED	LED SMD
CCT	3000 K
Duration LED (t. 25°C)	30000 h
CRI	> 80
Light beam	120°
Light beam flux	5000 lm
Useful light flux	2680 lm
Standby power	< 0.50