# moooi

# Perch Light Branch

**UMUT YAMAC** 



What is more poetic and elegantly captivating than a bird perched on a branch, flirting, singing and celebrating life? We all recognize this image and steal a moment from our precious time to admire this triumph of nature and beauty.

# Detailing




These sunlit birds are free to swing when softly touched. They gently glow and bring along the promise of spring.

## Colours



## Perch Light Branch / Large

## **Dimensions**



## Product

width 112cm | 44.1" неіднт 53cm | 20.9" дертн 41cm | 16.1" weight netto 9kg | 19.84lbs

## **Packaging**

width  $26.5 \, \mathrm{cm} \mid 10.4"$ Height  $57.5 \, \mathrm{cm} \mid 22.6"$ Cubage  $0.17 \, \mathrm{m}^3 \mid 6.11 \, \mathrm{ft}^3$ Length  $113.5 \, \mathrm{cm} \mid 44.7"$ Weight  $9 \, \mathrm{kg} \mid 19.84 \, \mathrm{lbs}$ 

## Technical CE

#### ADDITIONAL

Includes 3 small and 2 large birds. Minimum of 30cm/11,8" from ceiling. One straight connector included. Suspension poles included with set 1: 2x50cm, 2x15cm, 2x10cm (150cm total) finished in matching colour.

#### MATERIAL

Steel and aluminium frame with polycarbonate (PC) and synthetic paper birds.

ENEI	RGY	LΑ	BE	L
CIVE	naı	ᅜᄶ	ㅁㅁ	_

В

#### LIGHTSOURCE INCLUDED

Yes

## SHAPE

Linear

## FREQUENCY

50/60

#### LAMPHOLDER

LED (Solid state)

## CABLE COLOUR

Black

## CANOPY

Matching steel cylinder

## CRI

80

## LIGHT OUTPUT

560 lm

## LIGHTSOURCE TYPE

LED

#### NUMBER OF LIGHTSOURCES

5

#### **INPUT VOLTAGE**

180-240V

#### MAX POWER CONSUMPTION

15W

#### LIFETIME

50000 hours

## CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

#### COLOUR TEMPERATURE

3000 K

## LIGHT DIRECTION

All directions

## **DIMMING & LIGHTING CONTROL**

0-10V, 1-10V, Push / Pulse dim on Low Voltage (SELV), Potentiometer

See last page for more information about the dimming possibilities.



## Technical UL

## ADDITIONAL

Includes 3 small and 2 large birds. Minimum of 30cm/11,8" from ceiling. One straight connector included. Suspension poles included with set 1: 2x50cm, 2x15cm, 2x10cm (150cm total) finished in matching colour.

## MATERIAL

Steel and aluminium frame with polycarbonate (PC) and synthetic paper birds.

ENERGY LABEL LIGHTSOURCE TYPE

B LED

LIGHTSOURCE INCLUDED NUMBER OF LIGHTSOURCES

Yes

SHAPE INPUT VOLTAGE
Linear 90-305V

FREQUENCY MAX POWER CONSUMPTION

50/60 20W

LAMPHOLDER LIFETIME

LED (Solid state) 50000 hours

CABLE COLOURCABLE LENGTHBlack400cm | 157.5"

CANOPYCOLOUR TEMPERATUREMatching steel cylinder3000 K

CRI LIGHT DIRECTION
80 All directions

LIGHT OUTPUTDIMMING & LIGHTING CONTROL560 Im1-10V, PWM, Potentiometer

See last page for more information about the dimming possibilities.

C UL US