


RA 7 with lens 4,1W 3000K CRI90 36°

Design: Studio Tecnico Ivela



IP 44 IK 07



Product Code	Color
251-259BWN-21	Mat white

General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	RA 7 is a very thin ceiling downlight with PMMA lens designed for the last generation of COB LEDs. Easy to install in false ceilings, also with staves, from 1 to 30 mm. Protection rating IP44. LED drivers should be ordered separately.
Applications	Showrooms , Residential , Passage areas , Corridors

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 453lm 4,1W 3000K CRI90
Nominal lumens on thermal regime (lm)	453
LOR	83
Delivered lumen (lm)	376
Watt source (W)	4.1
Color temperature (K)	3000
CRI	CRI 90
Lamp type	LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Closing screen	Clear polycarbonate

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	PMMA lens
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate

Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	36°

Weight and dimension

Diameter (mm)	67
Cutout diameter (mm)	60
Recessed depth (mm)	23
Weight (Kg)	0.1
False ceiling thickness (mm)	1-30 mm

Accessories





Product Code 81-02408
Name Driver 350mA



Product Code 81-04003
Name Driver 350mA DALI dimmable

RA 7 with lens 6W 3000K CRI90 36°

Design: Studio Tecnico Ivela



IP 44 IK 07



Product Code	Color
251-259BWN-21	Mat white

General specifications

Product type	Downlights
Mounting type	Ceiling - recessed
Mounting location	Ceiling
Indoor/Outdoor light	Indoor
Description	RA 7 is a very thin ceiling downlight with PMMA lens designed for the last generation of COB LEDs. Easy to install in false ceilings, also with staves, from 1 to 30 mm. Protection rating IP44. LED drivers should be ordered separately.
Applications	Showrooms , Residential , Passage areas , Corridors

Lighting specifications

i Stated L.O.R. and delivered lumens values are related to standard beam angle versions

Lamp description	LED 619lm 6W 3000K CRI90
Nominal lumens on thermal regime (lm)	619
LOR	83
Delivered lumen (lm)	514
Watt source (W)	6
Color temperature (K)	3000
CRI	CRI 90
Lamp type	COB LED
Average lamp life (h)	L80B10 50.000
Photobiological risk group	RG1
Closing screen	Clear polycarbonate

Physical specifications

Body	Die-cast aluminium
Finishing	Polyester painted
Optic device	PMMA lens
Thermal dissipation	Passive

Electrical specifications

Driver availability	Separate
Driver mounting	Separate

Optical specifications

Light distribution	Symmetric
Emission	Direct
Aiming	Fixed
Light beam	36°

Weight and dimension

Diameter (mm)	67
Cutout diameter (mm)	60
Recessed depth (mm)	23
Weight (Kg)	0.1
False ceiling thickness (mm)	1-30 mm

Accessories



Product Code 81-04008
Name Driver 500mA dimmable on the mains and 1-10V



Product Code 81-04002
Name Driver 500mA DALI dimmable



Product Code 81-04087
Name Driver 500mA Wireless Bluetooth