

FLOS

■ F5921030 Black

Ray F2-S diffuser

Designed by Rodolfo Dordoni, 2006


Halogen - 250W



Floor lamp providing diffused lighting. Steel tube structure, welded, brushed and chrome-plated. Diffuser support in die-cast, polished and chrome-plated Zamak alloy. Injection-molded PA6 (nylon) lamp-cover. Color: white. Injection-molded PC (polycarbonate) inner diffuser. Color: 3% opal. Injection-molded elastic PVC (polyvinylchloride) feet. Lathe-shaped aluminum diffusers, painted white on the inside, and shiny white or black on the outside or gray-colored, blown and overlaid glass with glossy external finish. On the cable there is the electronic dimmer which allows the regulation of light brightness.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Floor
Environments	Indoor dry location
Light source type	Bulb
Light sources included	No
Lamp category	Halogen
Lamp holders	E27
Ilcos	HSGS
Number of lamps	1
Power (W)	250

Physical

Colour	Black
Length (mm)	430
Cord colour	Black
Cord length (mm)	1900
Net weight (kg)	5.95
Package volume (m3)	0.44
IP internal	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ LDT](#)

Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



FLOS

F5921009 White

Ray Floor 2

Designed by Rodolfo Dordoni, 2006


Halogen - 250W



Floor lamp providing diffused lighting. Steel tube structure, welded, brushed and chrome-plated. Diffuser support in die-cast, polished and chrome-plated Zamak alloy. Injection-molded PA6 (nylon) lamp-cover. Color: white. Injection-molded PC (polycarbonate) inner diffuser. Color: 3% opal. Injection-molded elastic PVC (polyvinylchloride) feet. Lathe-shaped aluminum diffusers, painted white on the inside, and shiny white or black on the outside or gray-colored, blown and overlaid glass with glossy external finish. On the cable there is the electronic dimmer which allows the regulation of light brightness.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Floor
Environments	Indoor dry location
Light source type	Bulb
Light sources included	No
Lamp category	Halogen
Lamp holders	E27
Ilcos	HSGS
Number of lamps	1
Power (W)	250

Physical

Colour	White
Length (mm)	430
Cord colour	Black
Cord length (mm)	1900
Net weight (kg)	5.95
Package volume (m3)	0.44
IP internal	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ LDT](#)

Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



FLOS

F5920020 Glass

Ray Floor 2

Designed by Rodolfo Dordoni, 2006


Halogen - 250W



Floor lamp providing diffused lighting. Steel tube structure, welded, brushed and chrome-plated. Diffuser support in die-cast, polished and chrome-plated Zamak alloy. Injection-molded PA6 (nylon) lamp-cover. Color: white. Injection-molded PC (polycarbonate) inner diffuser. Color: 3% opal. Injection-molded elastic PVC (polyvinylchloride) feet. Lathe-shaped aluminum diffusers, painted white on the inside, and shiny white or black on the outside or gray-colored, blown and overlaid glass with glossy external finish. On the cable there is the electronic dimmer which allows the regulation of light brightness.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Floor
Environments	Indoor dry location
Light source type	Bulb
Light sources included	No
Lamp category	Halogen
Lamp holders	E27
Ilcos	HSGS
Number of lamps	1
Power (W)	250

Physical

Colour	Glass
Length (mm)	430
Cord colour	Black
Cord length (mm)	1900
Net weight (kg)	9.1
Package volume (m3)	0.44
IP internal	20

Download

Mounting instructions [Download PDF](#)

Photometric Files

LDT / IES [Download LDT](#)


Technical Drawings

2D [Download ZIP](#)

3D [Download ZIP](#)



Bulbs



NOT INCLUDED

RF26998
LED 21W E27 2450lm 3000K
DIMMER



NOT INCLUDED

RF30429
LED Opal Lamp E27 21W 2700K
A65 Dimmable