

SUPERLOOP

OVERVIEW

A luminaire can be more than light alone. It can be functional, it can be decorative, it can be an eye catcher.

This family not only exists out of circles of light, it also brings circular and squared low voltage solutions for track lighting, so general and accent lighting can be combined within one family. In this way, Superloop allows you to choose 'functional', by mounting adjustable Spy modules on the round or square shaped base.

It allows you to choose 'decorative', by mounting the light emitting circle in a horizontal way, or it allows you to choose 'eye catcher', by carelessly hanging the circle of light vertical, as a statement.

SUPERLOOP SBL

Superloop HC with circular light has the ability to diffuse light all around. It represents a universal symbol with extensive options, a perfect circle of light, rolled out of 1 aluminium profile and seamlessly welded together. The specially designed current controlled LEDflex inside Superloop SBL allows it to be dimmed in various ways. Diameters up to 1700mm and finishes in different colours let you create the setting you want.

Similar to Superloop SBL HC, but more dramatic in expression, Superloop SBL VC grants the opportunity to use light in a different way. The vertical circle of light draws the attention and stimulates creativity.

For a more bold and expressive application you can opt for the Superloop VR, mounting the circle of light with a steel rod. Sculptural in presence, resonating with symbolism and respecting pure minimalism, the Superloop VR offers a very airy and remarkable element to your interior concept. Either as a single version or in a sequence to create striking vertical effects.

SUPERLOOP MDL

Superloop is also available in a round or square shape with a Delta Light custom engineered 48V low voltage track on the inside. This allows you to position and move light modules all around, offering maximum flexibility and allowing you to meet any need of the project.

The modules enable you to move from subtle functionality to very expressive or timeless elegance. The Flemish Gold and Flemish Bronze finishes or the Spot modules Vizir and Hedra offer you a way to upgrade the minimal appearance of the loop. By adding the Fix modules with down- or down-up light, combined with a clear or frosted glass, you can transform your Superloop into a modern chandelier. Looking for a more expressive and unique statement? Just plug and play with the ledtubes of the XY180 collection.

www.deltalight.com/superloop




reddot design award
winner

**GOOD
DESIGN**
award



INTERIOR
CEILING SURFACE / SUSPENDED

SUPERLOOP SBL				
LED 2786 - 8544 lm				
	Ø 700 mm	Ø 900 mm	Ø 1200 mm	Ø 1700 mm
 HC	✓	✓	✓	✓
 VC	✓	✓	✓	
 VR	✓	✓	✓	



SUPERLOOP MDL	
	
Ø 700 / 900 / 1200 / 1700 mm	□ 600 x 600 / 900 x 900 / 250 x 1100 / 250 x 1700 mm

ACCENT LIGHTING	 MIDISPY	✓
	 SPY	✓
	 VIZIR	✓
	 HEDRA	✓
GENERAL LIGHTING	 FIX	✓
	 FIX DOWN-UP	✓
	 FIX DOWN-UP GLASS	✓
	 XY180	✓

SUPERLOOP MDL





SUPERLOOP HC MDL



Ø695	Ø924	Ø1191	Ø1688
418 481 07 ◇	418 481 09 ◇	418 481 12 ◇	418 481 17 ◇
◇ B / FBR / FG			
INCL. 3 x CABLE SUSP. SINGLE AUTO. 3m INCL. 1 x CABLE 2 x 0,75mm ²			
◇ 2,3 IP20	◇ 3,0 IP20	◇ 3,9 IP20	◇ 5,5 IP20

SUPERLOOP S HC MDL



600 x 600	900 x 900	250 x 1100	250 x 1700
418 482 106 ◇	418 482 109 ◇	418 482 211 ◇	418 482 217 ◇
◇ B			
INCL. 4 x CABLE SUSP. SINGLE AUTO. 3m INCL. 1 x CABLE 2 x 0,75mm ²			
◇ 3,0 IP20	◇ 3,7 IP20	◇ 3,0 IP20	◇ 3,7 IP20

REQUIREMENTS ► SEE BELOW

LED POWER SUPPLY 48V-DC
or
POWERBOX 48V-DC L / H (FOR SUPERLOOP HC)
POWERBOX 48V-DC F (FOR SUPERLOOP SHC)


OPTIONS

CABLE BASE R ◇ ► **203 99 55** ANO / B / W
COVERSET R ◇ (Ø 62) ► **204 00 62** ANO / B / W
COVERSET R ◇ (Ø 90) ► **204 00 90** ANO / B / W
COVERSET R ◇ (Ø100) ► **204 00 100** ANO / B / W
CABLE BASE S ◇ ► **203 99 56** ANO / B / W
COVERSET S ◇ (62) ► **204 62 62** ANO / B / W
COVERSET S ◇ (80) ► **204 80 80** ANO / B / W
COVERSET S ◇ (90) ► **204 90 90** ANO / B / W
SMART 48 MODULATOR DIM9 ► **300 90 011**
SMART 48 MODULATOR WIRELESS DIM ► **300 90 012**

LED POWER SUPPLY

48V / 90W	48V / 100W	48V / 150W	48V / 240W
 171 x 63 x 38	 100 x 55 x 90	 240 x 60 x 49	 114 x 63 x 125
300 89 48 90	300 89 48 100	300 89 48 150	300 89 48 240
110-240V / 50-60Hz	110-240V / 50-60Hz	220-240V / 50-60Hz	100-240V / 50-60Hz
◇ IP67	◇ IP20		

POWERBOX L



48V-DC / 50W


418 48 050 ◇

◇ B

110-240V / 50-60Hz

◇ IP20

POWERBOX H



48V-DC / 100W


418 48 100 ◇

◇ B

110-240V / 50-60Hz

◇ IP20

POWERBOX F



48V-DC / 60W


300 48 060 ◇

◇ B

110-240V / 50-60Hz

◇ IP20

SUPERLOOP-MIDISPY MDL



3000K / CRI>80	3000K / CRI>90	2700K / CRI>80	2700K / CRI>90
LED 6W / 558lm / 48V-DC	LED 8,1W / 877lm / 48V-DC	LED 6W / 558lm / 48V-DC	LED 8,1W / 877lm / 48V-DC
20°	40°	20°	40°
418 262 832 MDL ◊	418 261 933 MDL ◊	418 262 822 MDL ◊	418 261 923 MDL ◊


◊ B

◊ 0,6 IP20

REQUIREMENTS

MIDISPY TUBE ► **414 03 00 B** / FBR / FG / MMAT / SG / W

SUPERLOOP-SPY MDL



3000K / CRI>90		2700K / CRI>90		2700-1800K / CRI>90
LED 10,4W / 1118lm / 48V-DC		LED 10,4W / 1073lm / 48V-DC		LED 9,5W / 760lm / 48V-DC
18°	33°	18°	33°	40°
418 361 811 931 MDL ◊	418 361 811 932 MDL ◊	418 361 811 921 MDL ◊	418 361 811 922 MDL ◊	418 361 1902 MDL ◊

◊ B / FBR / FG

◊ 0,5 IP20

◊ 0,5 IP20


REQUIREMENTS

SPY TUBE ► **414 01 00 B** / FBR / FG / MMAT / SG / W

ACCESSORIES

HONEYCOMB / LENS / GLASS 50
SPY PUNK SLEEVE


SUPERLOOP-SPY FOCUS LP MDL




3000K / CRI>90	2700K / CRI>90
LED 8,7W / 896lm / 48V-DC	LED 8,7W / 837lm / 48V-DC
8-43°	
20547 9300 ◊	20547 9200 ◊

◊ B / FBR / FG

◊ 0,6 IP20




SUPERLOOP-SPY FOCUS MP MDL




3000K / CRI>90	2700K / CRI>90
LED 17,9W / 1950lm / 48V-DC	LED 17,9W / 1874lm / 48V-DC
12-45°	
20546 9300 ◊	20546 9200 ◊

◊ B / FBR / FG

◊ 0,6 IP20



SUPERLOOP-SPY HP MDL



3000K / CRI>90	2700K / CRI>90
LED 16,8W / 2075lm / 48V-DC	LED 16,8W / 2000lm / 48V-DC
33°	
418 361 21 931 MDL ◊	418 361 21 921 MDL ◊
◊ B / FBR / FG	
◊ 0,5 IP20	


REQUIREMENTS

SPY TUBE ◊ ► **414 01 00 B** / FBR / FG / MMAT / SG / W

ACCESSORIES

HONEYCOMB / LENS / GLASS 50
SPY PUNK SLEEVE

SUPERLOOP-VIZIR MDL



3000K / CRI>80	3000K / CRI>90	2700K / CRI>80	2700K / CRI>90
LED 6W / 570lm / 48V-DC	LED 7,1W / 805lm / 48V-DC	LED 6W / 570lm / 48V-DC	LED 7,1W / 773lm / 48V-DC
15°	33°	15°	33°
418 367 831 MDL ◊	418 367 811 932 MDL ◊	418 367 821 MDL ◊	418 367 811 922 MDL ◊
◊ BBR / GC			
◊ 0,3 IP20			


REQUIREMENTS

VIZIR TUBE ◊ ► **473 01 00 B** / FBR / FG / W

ACCESSORIES

VIZIR HONEYCOMB / LENS / GLASS 40

SUPERLOOP-HEDRA MDL



3000K / CRI>80	3000K / CRI>90	2700K / CRI>80	2700K / CRI>90
LED 6W / 570lm / 48V-DC	LED 7,1W / 805lm / 48V-DC	LED 6W / 570lm / 48V-DC	LED 7,1W / 773lm / 48V-DC
15°	33°	15°	33°
418 368 831 MDL ◊	418 368 811 932 MDL ◊	418 368 821 MDL ◊	418 368 811 922 MDL ◊
◊ BBR / GC			
◊ 0,3 IP20			


REQUIREMENTS

VIZIR TUBE ◊ ► **473 01 00 B** / FBR / FG / W

ACCESSORIES


VIZIR HONEYCOMB / LENS / GLASS 40

SUPERLOOP-XY180 MDL




3000K / CRI>90
LED CLUSTER 8,9W / 1050lm / 48V-DC
418 561 93 MDL ◊
◊ B
◊ 0,4 IP20

SUPERLOOP-FIX 40 MDL



3000K / CRI>80	2700K / CRI>80
4,1W / 420lm / 48V-DC	
20°	
418 161 832 MDL ◊	418 161 822 MDL ◊
◊ B	
◊ 0,2 IP20	

SUPERLOOP-FIX 45 MDL




3000K / CRI>90	2700K / CRI>90
8,1W / 877lm / 48V-DC	
40°	
418 263 933 MDL ◊	418 263 923 MDL ◊
◊ B	
◊ 0,2 IP20	

REQUIREMENTS


MIDISPY TUBE ◊ ► **414 03 00 B** / FBR / FG / MMAT / SG / W

SUPERLOOP-FIX 40 DOWN-UP MDL



3000K / CRI>80	2700K / CRI>80
2,1W / 227lm (UP) / 48V-DC 4,1W / 420lm (DOWN) / 48V-DC	2,1W / 213lm (UP) / 48V-DC 4,1W / 420lm (DOWN) / 48V-DC
20°	
418 162 832 MDL ◊	418 162 822 MDL ◊
◊ B	
◊ 0,2 IP20	

SUPERLOOP-FIX 40 DOWN-UP GT MDL



3000K / CRI>80	2700K / CRI>80
2,1W / 227lm (UP) / 48V-DC 4,1W / 420lm (DOWN) / 48V-DC	2,1W / 213lm (UP) / 48V-DC 4,1W / 420lm (DOWN) / 48V-DC
20°	
418 163 832 MDL ◊	418 163 822 MDL ◊
◊ B	
◊ 0,2 IP20	

REQUIREMENTS


FIX 40 GLASS CLEAR ◊ ► **418 163 01**

FIX 40 GLASS FROSTED ◊ ► **418 163 02**






SUPERLOOP HC



SUPERLOOP HC



REQUIREMENTS ► SEE BELOW


LED POWER SUPPLY 500-700-900-1200-1700mA-DC
or
POWERBOX L / H

OPTIONS

CABLE BASE R ◊ ► **203 99 55** ANO / B / W
COVERSET R ◊ (Ø 62) ► **204 00 62** ANO / B / W
COVERSET R ◊ (Ø 90) ► **204 00 90** ANO / B / W
COVERSET R ◊ (Ø 100) ► **204 00 100** ANO / B / W

SBL			
Ø 695	Ø 924	Ø 1191	Ø 1688
3000K / CRI>90			
LED FLEX 20,5W / 2786lm / 500mA LED FLEX 30,3W / 3510lm / 700mA	LED FLEX 28,9W / 3845lm / 700mA LED FLEX 38,7W / 4570lm / 900mA	LED FLEX 37,2W / 4951lm / 900mA LED FLEX 51,9W / 6027lm / 1200mA	LED FLEX 51,6W / 6721lm / 1200mA LED FLEX 73,5W / 8544lm / 1700mA
321 107 93 ◊	321 109 93 ◊	321 112 93 ◊	321 117 93 ◊
◊ B / FBR / FG / W			
INCL.3 x CABLE SUSP. SINGLE AUTO. 3m INCL.1 x CABLE 2 x 0,75mm ²			
IP20	IP20	IP20	IP20

SUPERLOOP HC SPR



REQUIREMENTS ► SEE BELOW

LED POWER SUPPLY 500-700-900-1200-1700mA-DC
or
POWERBOX L / H

OPTIONS

CABLE BASE R ◊ ► **203 99 55** ANO / B / W
COVERSET R ◊ (Ø 62) ► **204 00 62** ANO / B / W
COVERSET R ◊ (Ø 90) ► **204 00 90** ANO / B / W
COVERSET R ◊ (Ø 100) ► **204 00 100** ANO / B / W

SPR			
Ø 695	Ø 924	Ø 1191	Ø 1688
3000K / CRI>90			
LED FLEX 20,5W / 2786lm / 500mA LED FLEX 30,3W / 3510lm / 700mA	LED FLEX 28,9W / 3845lm / 700mA LED FLEX 38,7W / 4570lm / 900mA	LED FLEX 37,2W / 4951lm / 900mA LED FLEX 51,9W / 6027lm / 1200mA	LED FLEX 51,6W / 6721lm / 1200mA LED FLEX 73,5W / 8544lm / 1700mA
321 207 93 ◊	321 209 93 ◊	321 212 93 ◊	321 217 93 ◊
◊ B / FBR / FG / W			
INCL.3 x CABLE SUSP. SINGLE AUTO. 3m INCL.1 x CABLE 2 x 0,75mm ²			
IP20	IP20	IP20	IP20


LED POWER SUPPLY

DIM1: DIMMING BY 1-10V / DIM5: DIMMING BY DALI

500mA-DC / 31W DIM1	700mA-DC / 31W DIM1	700mA-DC / 50W DIM5	900mA-DC / 50W DIM5	1200mA-DC / 120W DIM1	1200mA-DC / 60W DIM5	1700mA-DC / 120W DIM1
141 x 43 x 30 Ø60	141 x 43 x 30 Ø60	204 x 50 x 33 Ø66	204 x 50 x 33 Ø66	240 x 59 x 40 Ø80	220 x 85 x 31 Ø95	167 x 57 x 32 Ø70
300 90 127	300 90 128	300 90 131	300 90 129	300 90 132	300 90 130	300 90 133
220-240V / 50-60Hz	220-240V / 50-60Hz	220-240V / 50-60Hz	220-240V / 50-60Hz	220-240V / 50-60Hz	220-240V / 0/50-60Hz	220-240V / 50-60Hz


IP20

POWERBOX L




500mA-DC DIM1	700mA-DC DIM1	700mA-DC DIM5	1200mA-DC DIM1	1700mA-DC DIM1	900mA-DC DIM5	1200mA-DC DIM5
321 55 205 ED1 ◊	321 55 207 ED1 ◊	321 55 307 ED5 ◊	321 55 312 ED1 ◊	321 55 317 ED1 ◊	20548 0015 ◊	20548 0025 ◊
◊ B / W		◊ B / W		◊ B / W		
220-240V / 50-60Hz		220-240V / 50-60Hz		110-240V / 50-60Hz		
IP20		IP20		IP20		

POWERBOX H8



POWERBOX H9



SUPERLOOP VC



SUPERLOOP VC



Ø 695
Ø 924
Ø 1191

REQUIREMENTS ► SEE BELOW
LED POWER SUPPLY 500-700-900-1200mA-DC
or
POWERBOX L / H

Ø 695	Ø 924	Ø 1191
3000K / CRI>90		
LED FLEX 20,5W / 2786lm / 500mA LED FLEX 30,3W / 3510lm / 700mA	LED FLEX 28,9W / 3845lm / 700mA LED FLEX 38,7W / 4570lm / 900mA	LED FLEX 37,2W / 4951lm / 900mA LED FLEX 51,9W / 6027lm / 1200mA
321 507 93 ◊	321 509 93 ◊	321 512 93 ◊
◊ B / FBR / FG / W		
INCL. 2 x CABLE SUSP. SINGLE AUTO. 3m INCL. 1 x CABLE 2 x 0,75mm ²		
◊ 2,7 IP20	◊ 3,4 IP20	◊ 4,3 IP20


LED POWER SUPPLY

DIM1: DIMMING BY 1-10V / DIM5: DIMMING BY DALI


500mA-DC / 31W DIM1	700mA-DC / 31W DIM1	700mA-DC / 50W DIM5	900mA-DC / 50W DIM5	1200mA-DC / 120W DIM1	1200mA-DC / 60W DIM5
141 x 43 x 30	141 x 43 x 30	204 x 50 x 33	204 x 50 x 33	240 x 59 x 40	220 x 85 x 31
Ø60	Ø60	Ø66	Ø66	Ø80	Ø95
300 90 127	300 90 128	300 90 131	300 90 129	300 90 132	300 90 130
220-240V / 50-60Hz					220-240V / 0/50-60Hz

◻ IP20


POWERBOX L



POWERBOX H8



POWERBOX H9



500mA-DC DIM1	700mA-DC DIM1	700mA-DC DIM5	1200mA-DC DIM1	900mA-DC DIM5	1200mA-DC DIM5
321 55 205 ED1 ◊	321 55 207 ED1 ◊	321 55 307 ED5 ◊	321 55 312 ED1 ◊	20548 0015 ◊	20548 0025 ◊
◊ B / W		◊ B / W		◊ B / W	
220-240V / 50-60Hz		220-240V / 50-60Hz	110-240V / 50-60Hz	110-240V / 50-60Hz	220-240V / 50-60Hz
◻ IP20		◻ IP20	◊ IP20	◻ IP20	


SUPERLOOP VR



INTERIOR
CEILING SURFACE / SUSPENDED

WIRELESS
CONTROL
Suitable
for all
dimmable
luminaires.
CTRL
DELTA
R
TECHNICAL DATA ► PAG TEC 4

SUPERLOOP VR



Ø 695
Ø 924
Ø 1191

REQUIREMENTS ► SEE BELOW
LED POWER SUPPLY 500-700-900-1200mA-DC

Ø 695	Ø 924	Ø 1191
3000K / CRI>90		
LED FLEX 20,5W / 2786lm / 500mA LED FLEX 30,3W / 3510lm / 700mA	LED FLEX 28,9W / 3845lm / 700mA LED FLEX 38,7W / 4570lm / 900mA	LED FLEX 37,2W / 4951lm / 900mA LED FLEX 51,9W / 6027lm / 1200mA
321 407 93 ◇	321 409 93 ◇	321 412 93 ◇
◇ B / FBR / FG / W		
INCL. 1 x ROD SUSPENSION 0,65m INCL. 1 x CABLE 2 x 0,75mm²		
3,1 IP20	3,8 IP20	4,7 IP20

LED POWER SUPPLY

DIM1: DIMMING BY 1-10V / DIM5: DIMMING BY DALI

500mA-DC / 31W DIM1	700mA-DC / 31W DIM1	700mA-DC / 50W DIM5	900mA-DC / 50W DIM5	1200mA-DC / 120W DIM1	1200mA-DC / 60W DIM5
141 x 43 x 30	141 x 43 x 30	204 x 50 x 33	204 x 50 x 33	240 x 59 x 40	220 x 85 x 31
Ø60	Ø60	Ø66	Ø66	Ø80	Ø95
300 90 127	300 90 128	300 90 131	300 90 129	300 90 132	300 90 130

220-240V / 50-60Hz

220-240V / 0/50-60Hz

IP20



INTERIOR DESIGNER: VENKO DESIGN
ELECTRICAL ENGINEER: EDM BROSSE
FLOORING: TYP
SPEAKER: KOSHER SOUND

INTERIOR
CEILING SURFACE / SUSPENDED



INTERIOR DESIGNER: VENKO DESIGN
ELECTRICAL ENGINEER: ECM GROUP
BUILDER: INTREX
PHOTOGRAPHY: CHRIS SANOS











INTERIOR
CEILING SURFACE / SUSPENDED



INTERIEURBURO PEDRO VERHUE