



Design By Ramos & Bassols


Top is a wall lamp that comes in a range of balanced colours that help to create very warm atmospheres. The Top collection offers indirect light that is confined within its diameter, forming a contrast with the outer part of the lamp.

Model Sheet









Finish

36 Soft Pink NCS S 1010-Y50R



40 Blue L1 NCS S 3010-B



NCS S 0300-N 47 Green L1

NCS S 4005-G80Y

LED temperature color

2700 K

Dimming

On/ Off

Instalation type

Surface Canopy

Materials

Body: Aluminum Diffuser: Aluminum

Plate: Steel

Light source

1 x LED PLATE 5,5W 150mA

LED

CRI>90 550 lm 100

2700 K


Driver

CC - Constant Current 150 100~240 V 50/60 HZ











Application

Wall Lamps

Packaging

1 Box

0.21 m x 0.2 m x 0.13 m Gross weigth 0.8 Net weigth 0.5 Vol. 0.0054

Lighting effect

General Lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



These photometric data refer to finish 10. If you need the photometrics of other finishes please go to Download

Efficiency Coordinate System Total Flux Maximum Value

38.37 lm/W CG 263,64lm 53,87cd

Other Applications





All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty







Design By Ramos & Bassols


Top is a wall lamp that comes in a range of balanced colours that help to create very warm atmospheres. The Top collection offers indirect light that is confined within its diameter, forming a contrast with the outer part of the lamp.

Model Sheet









Finish

40 Blue L1 NCS S 3010-B



47 Green L1 NCS S 4005-G80Y



10 White NCS S 0300-N



36 Soft Pink NCS S 1010-Y50R

LED temperature color

2700 K

Dimming

1-10V PUSH

Optional Casambi

Min. quantity, upcharge and extra

lead time apply [EN]

Instalation type

Surface Canopy

Materials

Body: Aluminum Diffuser: Aluminum Ceiling rose: Steel

Light source

1 x LED PLATE 18,3W 500mA

LED


CRI>90 2050 lm 112 2700 K

Driver

CC - Constant Current 500 220~240 V 50/60 HZ









[P20] [50-60Hz

Application

Wall Lamps

Packaging

0.558 m x 0.558 m x 0.255 m

Gross weigth 1.8 Net weigth 1.5 Vol. 0.0793

Lighting effect

General Lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



These photometric data refer to finish 47. If you need the photometrics of other finishes please go to Download

Efficiency Coordinate System Total Flux Maximum Value

21.06 lm/W CG 349.72 lm 112.03 cd

Other Applications





All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty





V/|3|/\


Design By Ramos & Bassols

Top is a ceiling or wall lamp that comes in a range of balanced colours that help to create very warm atmospheres. The Top collection offers indirect light that is confined within its diameter, forming a contrast with the outer part of the lamp.

Model Sheet







Finish 10 White NCS S 0300-N 47 Green L1 NCS S 4005-G80Y 36 Soft Pink NCS S 1010-Y50R

LED temperature color

2700 K

40 Blue L1

Dimming DALI 1-10V Push
Optional Casambi

Min. quantity, upcharge and extra

lead time apply [EN]

Instalation type Surface Canopy

Materials Body: Aluminum
Diffuser: Aluminum
Ceiling rose: Steel

Light source 1 x LED PLATE 26,4W 700mA

Ε

LED CRI>90 2880 lm 109.10

2700 K

Driver CC - Constant Current 700 220~240 V 50/60 HZ

220-240 1 30/00 112

[IP20] [50-60Hz]

Application Ceiling Lamps

Packaging 1 Box 0.76 m x 0.76 m x 0.27 m

Gross weigth 3.13 Net weigth 2.5 Vol. 0.1559

Lighting effect

General Lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric Dato

These photometric data refer to finish 40. If you need the photometrics of other finishes please go to Download.

Efficiency 15.60 lm/W
Coordinate System CG
Total Flux 478.39 lm
Maximum Value 84.15 cd

Other Applications





All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty







Design By Ramos & Bassols


Top is a ceiling lamp with surface installation. It features simple lines that blend in with the ceiling as much as possible. The light reflected by the glass diffuser is confined within the rosette, as if the light were framed.

Model Sheet











47 Green L1 NCS S 4005-G80Y

40 Blue L1 NCS S 3010-B

10 White NCS S 0300-N 36 Soft Pink NCS S 1010-Y50R

LED temperature color

2700 K

Dimming DALI 1-10V Push

Optional Casambi Min. quantity, upcharge and extra

lead time apply [EN]

Instalation type Surface Canopy

Materials Body: Aluminum

> Ceiling rose: Aluminum Diffuser: Opal blown-glass

Light source 3 x LED 13,4W 700mA

CRI>90 3300 lm 82.08 LED

2700 K

CC - Constant Current 700 220~240 V 50/60 HZ Driver

IP20 Dry Location 50-60Hz

Ceiling Lamps **Application**

Packaging 1.12 m x 1.12 m x 0.345 m

Gross weigth 7.7 Net weigth 5.3 Vol. 0.4327

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



These photometric data refer to finish 36. If you need the photometrics of other finishes please go to Download

Efficiency Coordinate System Total Flux Maximum Value

66.69 lm/W CG 3103.46 lm 813.96 c

Other Applications





All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty