Design by Jordi Vilardell & Meritxell Vidal.



Reference

6005.

Application

Floor Lamps

Installation type

Surface

Description

Suite is a floor lamp that boasts different functions, where matter and light are integrated in a single body. Suite boasts different stands, as well as LED lighting and a USB charging station. Designed by Jordi Vilardell & Meritxell Vidal. Available in two finishes: dark brown and white.

Diffuser

Polycarbonate diffuser

Finish



6005-14. Matt dark-brown

Matt white lacquer

lacquer

Sketch



Electrical characteristics

8 x LED STRIP 24V 1,63W

Total 13.0 W





Physical characteristics

1 Box / $0.61 \times 0.54 \times 1.37 \text{ m.}$ / Vol. 0.4445 m^3 / Gross weight 24.8 kg. / Net weight 22.3 kg.

Installation and assembly

Please, see the installation manual

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.




Photometric data

Efficiency: 54.29% Coordinate system : CG Total flux: 1054.72 lm

Isolux: Isolux (Floor) Light position : X=0.00m Y=0.00m Z=1.30m

Maximum value : 179.12 cd/klm Light position : C=140.00 G=30.00 Symmetry on the planes : Asymmetric











Design by Jordi Vilardell & Meritxell Vidal.



Reference

6006.

Application

Floor Lamps

Installation type

Surface

Description

Suite is a floor lamp that boasts different functions, where matter and light are integrated in a single body. Suite boasts different stands, as well as LED lighting and a USB charging station. Designed by Jordi Vilardell & Meritxell Vidal. Available in two finishes: dark brown and white.

Diffuser

Polycarbonate diffuser

Finish



6006-14. Matt

dark-brown lacquer

Matt white lacquer

Sketch



Electrical characteristics

8 x LED STRIP 24V 1,63W AND

1 x LED 4,5W 350mA



Total 17.5 W





Physical characteristics

1 Box / 0.61 x 0.54 x 1.37 m. / Vol. 0.4445 $\ensuremath{\text{m}}^3$ / Gross weight 24.4 kg. / Net weight 22.0 kg.

Installation and assembly

Please, see the installation manual

Light distribution

General lighting


Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency: 54.64% Isolux: Isolux (Floor) Coordinate system : CG Light position :

Total flux : 1480.72 lm Maximum value : 130.00 cd/klm Light position: C=140.00 G=30.00



X=0.00m Y=0.00m Z=1.30m









Design by Jordi Vilardell & Meritxell Vidal.



Reference

6007.

Application

Floor Lamps

Installation type

Surface

Description

Suite is a floor lamp that boasts different functions, where matter and light are integrated in a single body. Suite boasts different stands, as well as LED lighting and a USB charging station. Designed by Jordi Vilardell & Meritxell Vidal. Available in two finishes: dark brown and white.

Diffuser

Polycarbonate diffuser


Finish



6007-14. 6007-93. Matt Matt white dark-brown lacquer

lacquer

Sketch



Electrical characteristics

8 x LED STRIP 24V 1,63W AND

1 x LED 4,5W 350mA



Total 17.5 W





Physical characteristics

1 Box / $0.61 \times 0.54 \times 1.37 \text{ m.}$ / Vol. 0.4513 m^3 / Gross weight 23.6 kg. / Net weight 17.0 kg.

Installation and assembly

Please, see the installation manual

Light distribution

Reading

Lamp having a light beam whose main function is to supply sufficient light for reading.




Photometric data

Efficiency: 42.55% Coordinate system : CG Total flux: 1480.72 lm

Maximum value : 152.64 cd/klm

Light position : C=320.00 G=30.00 Symmetry on the planes : Asymmetric



Isolux: Isolux (Floor) Light position :

X=0.00m Y=0.00m Z=1.30m









Design by Jordi Vilardell & Meritxell Vidal.



Reference

6010.

Application

Floor Lamps

Installation type

Surface

Description

Suite is a floor lamp that boasts different functions, where matter and light are integrated in a single body. Suite boasts different stands, as well as LED lighting and a USB charging station. Designed by Jordi Vilardell & Meritxell Vidal. Available in two finishes: dark brown and white.

Diffuser

Polycarbonate diffuser

Finish




6010-14. 6010-93. Matt Matt white

lacquer

dark-brown lacquer

Sketch



Electrical characteristics

6 x LED STRIP 24V 1,63W

Total 9.8 W





Physical characteristics

1 Box / $0.61 \times 0.54 \times 1.10 \text{ m.}$ / Vol. 0.3274 m^3 / Gross weight 21.9 kg. / Net weight 19.7 kg.

Installation and assembly

Please, see the installation manual

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.

Photometric data


Efficiency: 52.86% Coordinate system : CG Total flux: 791.00 lm

X=0.00m Y=0.00m Z=0.94m

Isolux : Isolux (Floor)

Light position :

Maximum value : 170.48 cd/klm Light position : C=190.00 G=40.00 Symmetry on the planes : Asymmetric











Design by Jordi Vilardell & Meritxell Vidal.



Reference

6011.

Application

Floor Lamps

Installation type

Surface

Description

Suite is a floor lamp that boasts different functions, where matter and light are integrated in a single body. Suite boasts different stands, as well as LED lighting and a USB charging station. Designed by Jordi Vilardell & Meritxell Vidal. Available in two finishes: dark brown and white.

Diffuser

Polycarbonate diffuser

Finish




6011-14. 6011-93. Matt Matt white

lacquer

dark-brown lacquer

Sketch



Electrical characteristics

6 x LED STRIP 24V 1,63W AND

1 x LED 4,5W 350mA



Total 14.3 W





Physical characteristics

1 Box / 0.61 x 0.54 x 1.10 m. / Vol. 0.3274 $m^3\,/$ Gross weight 22.3 kg. / Net weight 20.1 kg.

Installation and assembly

Please, see the installation manual

Light distribution


General lighting

Lamp for general lighting that equally distributes the light in all directions.

Photometric data

Efficiency: 54.30% Isolux: Isolux (Floor) ${\it Coordinate \ system: CG}$ Light position : Total flux : 1217.00 lm X=0.00m Y=0.00m Z=0.94m

Maximum value : 111.54 cd/klm Light position: C=190.00 G=40.00









Design by Jordi Vilardell & Meritxell Vidal.



Reference

6012.

Application

Floor Lamps

Installation type

Surface

Description

Suite is a floor lamp that boasts different functions, where matter and light are integrated in a single body. Suite boasts different stands, as well as LED lighting and a USB charging station. Designed by Jordi Vilardell & Meritxell Vidal. Available in two finishes: dark brown and white.

Diffuser

Polycarbonate diffuser


Finish



6012-14. 6012-93. Matt Matt white

dark-brown lacquer lacquer

Sketch



Electrical characteristics

6 x LED STRIP 24V 1,63W

1 x LED 4,5W 350mA



Total 14.3 W





Physical characteristics

1 Box / $0.61 \times 0.54 \times 1.37 \text{ m.}$ / Vol. 0.4445 m^3 / Gross weight 22.2 kg. / Net weight 20.0 kg.

Installation and assembly

Please, see the installation manual

Light distribution

Reading

Lamp having a light beam whose main function is to supply sufficient light for reading.

Isolux : Isolux (Floor)

X=0.00m Y=0.00m Z=1.10m


Light position :

Photometric data

Efficiency: 38.31% Coordinate system : CG Total flux : 1217.00 lm

Maximum value : 143.19 cd/klm

Light position : C=280.00 G=30.00 Symmetry on the planes : Asymmetric











Design by Jordi Vilardell & Meritxell Vidal.



Reference

6027.

Application

Table Lamps

Installation type

Surface

Description

Suite is a table lamp attached to the wall that boasts different functions, where matter and light are integrated in a single body. Suite boasts different stands, as well as LED lighting and a USB charging station. Designed by Jordi Vilardell & Meritxell Vidal. Available in two finishes: dark brown and white.

Diffuser

Polycarbonate diffuser


Finish





lacquer

Sketch



Electrical characteristics

8 x LED STRIP 24V 1,63W

1 x LED 4,5W 350mA



Total 17.5 W





Physical characteristics

1 Box / 0.61 x 0.54 x 1.37 m. / Vol. 0.4445 m³ / Gross weight 11.7 kg. / Net weight 10.5 kg.


Installation and assembly

Please, see the installation manual

Light distribution

Reading

Lamp having a light beam whose main function is to supply sufficient light for reading.











Design by Jordi Vilardell & Meritxell Vidal.



Reference

6032.

Application

Floor Lamps

Installation type

Surface

Description

Suite is a table lamp attached to the wall that boasts different functions, where matter and light are integrated in a single body. Suite boasts different stands, as well as LED lighting and a USB charging station. Designed by Jordi Vilardell & Meritxell Vidal. Available in two finishes: dark brown and white.

Diffuser

Polycarbonate diffuser

Finish




6032-14. Matt

6032-93. Matt white dark-brown lacguer

lacquer

Sketch



Electrical characteristics


6 x LED STRIP 24V 1,63W AND

1 x LED 4,5W 350mA



Total 14.3 W





Physical characteristics

1 Box / 0.61 x 0.54 x 1.10 m. / Vol. 0.3274 m^3 / Gross weight 9.7 kg. / Net weight 8.7 kg.

Installation and assembly

Please, see the installation manual

Light distribution

Reading

Lamp having a light beam whose main function is to supply sufficient light for reading.

Photometric data

Efficiency: 38.11% Coordinate system : CG Total flux : 1217.00 lm

Maximum value : 145.96 cd/klm Light position: C=100.00 G=30.00 Isolux : Isolux (Floor) Light position:

X=0.00m Y=0.00m Z=0.90m

