

Wallwasher12 RGB

PROLED®



The PROLED WALLWASHER12 RGB is ideal for the illumination of large surfaces, e.g. buildings or walls in outdoor areas. They are also suitable for ambient lighting in indoor applications. Because of the RGB 3-in-1 high power LEDs the WALLWASHER12 RGB offers homogeneous colormixing.

- dimmable, autom. colour change, DMX 512, DALI, 1-10 V controllable by MBNLED RGB MULTI power supplies or MBNLED PRO CONTROLLER RGB MULTI

> EULUMDAT/IES information

TECHNICAL DATA

IP classification:	IP65 (for outdoor use)
Power source:	24 VDC Common Cathode (CC)
Housing:	powder coated aluminium grey (RAL 7024), 7 mm tempered glass
Electrical connection:	1x cable 2 m H05RN-F 4x 0,75 mm ² with 4-PIN IP68 connector male
Operating temperature range:	-10° C till +45° C

PHOTOMETRIC DATA

LED type:	HARVATEK RGB 3-in-1 LEDs
Luminous flux:	red 250 Lumen green 550 Lumen blue 150 Lumen r+g+b 920 Lumen
Wave length:	red 620 nm green 526 nm blue 467 nm
Beam angle:	30°

Due to conditions of production photometric data can vary from production batch to production batch within the EU directive.

PRODUCT TYPES						
order code	colour	LED pcs	LED power	power consumption*	weight	EEI
order code	colour	LED pcs	LED power	power consumption*	weight	EEI
L1308	RGB	12	36 Watt	36 Watt	2,3 kg	B

*Actual power consumption