

Date _____

Name _____

Client _____



Project Name _____

Quote# _____

Type/Quantity _____

B-LINER 65 P630 EVG DIM1
384 01 62 ED1

[Weblink](#)



Available colors: ALU ANODISED (384 01 62 ED1 ANO)
 WHITE (384 01 62 ED1 W)

- DOWN-UP
- INCL.LED CLUSTER DOWN 32W / CRI>80 / 3000K / 3920lm
- INCL.LED CLUSTER UP 16W / CRI>80 / 3000K / 1960lm
- INCL.LED POWER SUPPLY DIM1
- INCL.2 x PC SBL
- INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1.6m
- CABLING 2 CIRCUITS
- INCL.1 x CABLE 5 x 0.75mm²
- INCL.1 x CABLE 2 x 0.75mm²
- DOWN DIMMABLE BY 1-10V CONTROL

LED Technics: Light source: 5880 lm // 48 W // 122 lm/W
 Luminaire: 5090 lm // 55 W // 92 lm/W

110-240V / 50-60Hz

Class: I

Weight: 2.5 KG

Protection level: IP20

Minimum distance: n.a.

Options: CABLE BASE R / S
 COVERSET R 62-90-100 / S 62-80-90







For detailed installation instructions, please consult the manual. [384_01_62_HAND.pdf](#)

B-LINER 65 P630 EVG DIM1

384 01 62 ED1



Related references

COVERSETS

<p>Weblink / Specsheet</p>  <p>COVERSET R 100 204 00 100</p>	<p>Weblink / Specsheet</p>  <p>COVERSET R 62 204 00 62</p>	<p>Weblink / Specsheet</p>  <p>COVERSET R 90 204 00 90</p>	<p>Weblink / Specsheet</p>  <p>COVERSET S 62 204 62 62</p>
<p>Weblink / Specsheet</p>  <p>COVERSET S 80 204 80 80</p>	<p>Weblink / Specsheet</p>  <p>COVERSET S 90 204 90 90</p>		

Related references

SUSPENSION PARTS

<p>Weblink / Specsheet</p>  <p>CABLE BASE R 203 99 55</p>	<p>Weblink / Specsheet</p>  <p>CABLE BASE S 203 99 56</p>
--	--

B-LINER 65 P630 EVG DIM1
384 01 62 ED1

Project picture

