

Date

Name

Client



Project Name

Quote#

Type/Quantity

**LOGIC MINI W R**  
**304 30 12**

[Weblink](#)









Cutout shape/size:	55 mm
Recessed depth:	50 mm
Available colors:	ALU GREY (304 30 12 A) WHITE (304 30 12 W)
INCL. 1 x POWERLED WHITE 0,6W / 3000K / 40lm EXCL. LED POWER SUPPLY 24V-DC Not Dimmable	
LED Technics:	Light source: 45 lm // 67 lm/W Luminaire: 4 lm // 2 W // 2 lm/W
24V-DC	
Class:	III
Weight:	0.2 KG
Protection level:	IP54
Minimum distance:	n.a.
Options:	LED POWER SUPPLY 24V-DC CONCRETE BOX 188

For detailed installation instructions, please consult the manual. [304\\_30\\_12\\_HAND.pdf](#)

**LOGIC MINI W R**  
304 30 12


**Related references**

**LED POWER SUPPLIES**

<p><a href="#">Weblink / Specsheet</a></p>  <p>211 66 42</p> <p>LED POWER SUPPLY 24V-DC / 150W 300 89 24 150 220-240V / 0 50-60Hz Number of luminaires: 225</p>	<p><a href="#">Weblink / Specsheet</a></p>  <p>146 19 55</p> <p>LED POWER SUPPLY 24V-DC / 20W 300 89 24 20 110-240V / 0 50-60Hz Number of luminaires: 30</p>	<p><a href="#">Weblink / Specsheet</a></p>  <p>163 32 43</p> <p>LED POWER SUPPLY 24V-DC / 40W 300 89 24 40 110-240V / 50-60Hz Number of luminaires: 60</p>	<p><a href="#">Weblink / Specsheet</a></p>  <p>163 32 43</p> <p>LED POWER SUPPLY 24V-DC / 60W 300 89 24 60 110-240V / 50-60Hz Number of luminaires: 90</p>
<p><a href="#">Weblink / Specsheet</a></p>  <p>93 78 56</p> <p>LED POWER SUPPLY 24V-DC / 60W DIN 300 89 24 61 110-240V / 50-60Hz Number of luminaires: 90</p>	<p><a href="#">Weblink / Specsheet</a></p>  <p>250 34 50</p> <p>LED POWER SUPPLY 24V-DC / 80W DIM1 300 89 24 80 220-240V / 50-60Hz Number of luminaires: 120</p>		

**Related references**

**CONCRETE BOXES**

<p><a href="#">Weblink / Specsheet</a></p>  <p>90 90 10 65 Ø60</p> <p>CONCRETE BOX 188 270 11 188</p>
--

LOGIC MINI W R  
304 30 12

## Project picture

