

Flat


5945

Design By Ichiro Iwasaki

The Flat floor lamp offers multiple functionality; material and light are integrated in a single body. The Flat collection contains various planes of light that rise up to become self-illuminating supports.

VIBIA

Model Sheet



Finish

- 47 Green L1
NCS S 4005-G80Y
- 13 White Grey L1
NCS S 1000-N

LED temperature color 2700 K

Dimming PUSH

Installation type Surface Canopy

Materials

- Body: Steel
- Base: Steel
- Head: Aluminium
- Reflector: Aluminum

Light source 2 x LED PLATE 7W 400mA
F

LED CRI>90 2400 lm 171.4
2700 K

Driver CC - Constant Current 400
100~240 V 50/60 HZ

Remarks 24V transformer at plug

☐ ☒ **Dimmable** **LED**
IP20 **Bi-volt** **50-60Hz** **PUSH**

Application Floor Lamps


Packaging

- 1 Box
- 0.72 m x 0.72 m x 0.96 m
- Gross weight 48
- Net weight 15.25
- Vol. 0.4976

Lighting effect

General Lighting


Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric Data

Efficiency 64.98 lm/W
Coordinate System CG
Total Flux 1280.18 lm
Maximum Value 343.56 cd

Other Applications



All of our products come with a five-year warranty.
Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com

Flat


5950

Design By Ichiro Iwasaki

The Flat floor lamp offers multiple functionality; material and light are integrated in a single body. The Flat collection contains various planes of light that rise up to become self-illuminating supports.

VIBIA

Model Sheet



Finish 10 White
NCS S 0300-N

LED temperature color 2700 K

Dimming PUSH

Installation type Surface Canopy

Materials Body: Steel
Base: Steel
Head: Aluminium
Reflector: Aluminum

Light source 1 x LED PLATE 7W 400mA
F

LED CRI>90 1200 lm 171.4
2700 K

Driver CC - Constant Current 400
100~240 V 50/60 HZ

Remarks 24V transformer at plug

☐ F ☐ Dimmer ☐ LED
☐ IP20 ☐ Bi-volt ☐ 50-60Hz ☐ PUSH

Application Floor Lamps

Packaging 1 Box
0.72 m x 0.72 m x 0.5 m
Gross weight 14.6
Net weight 12.71
Vol. 0.2592

Lighting effect

General Lighting


Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric Data

Efficiency 51.15 lm/W
Coordinate System CG
Total Flux 455.40 lm
Maximum Value 102.48 cd

Other Applications



All of our products come with a five-year warranty.
Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6, 08850 Gavà, Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com