

Flat


5955

Design By Ichiro Iwasaki

The Flat floor lamp offers multiple functionality; material and light are integrated in a single body. The Flat collection contains various planes of light that rise up to become self-illuminating supports.

VIBIA

Model Sheet



Finish

- 47 Green L1
NCS S 4005-G80Y
- 11 Black
NCS S 8500N
- 37 Terra Red
NCS S 4040-Y70R

LED temperature color 2700 K

Dimming PUSH

Installation type Surface Canopy

Materials
Body: Steel
Base: Steel
Head: Aluminium
Reflector: Aluminum

Light source
1 x LED PLATE 7W 400mA
F

LED
CRI>90 1200 lm 171.4
2700 K

Driver
CC - Constant Current 400
100-240 V 50/60 HZ

Remarks
24V transformer at plug

☐ F ☐ Dimmer ☐ LED
☐ IP20 ☐ Bi-volt ☐ 50-60Hz ☐ PUSH


Application
Floor Lamps

Packaging
1 Box
0.72 m x 0.72 m x 0.96 m
Gross weight 11.6
Net weight 3.5
Vol. 0.4976

Lighting effect

General Lighting


Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric Data

Efficiency 76.96 lm/W
Coordinate System CG
Total Flux 682.09 lm
Maximum Value 275.02 cd

Other Applications



All of our products come with a five-year warranty.
Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6, 08850 Gavà, Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com

Flat


5957

Design By Ichiro Iwasaki

The Flat floor lamp offers multiple functionality; material and light are integrated in a single body. The Flat collection contains various planes of light that rise up to become self-illuminating supports.

VIBIA

Model Sheet



Finish

- 13 White Grey L1
NCS S 1000-N
- 47 Green L1
NCS S 4005-G80Y

LED temperature color 2700 K

Dimming PUSH

Installation type Surface Canopy

Materials

- Body: Steel
- Base: Steel
- Head: Aluminium
- Reflector: Aluminum

Light source 1 x LED PLATE 7W 400mA
F

LED CRI>90 1200 lm 171.4
2700 K

Driver CC - Constant Current 400
100~240 V 50/60 HZ

Remarks 24V transformer at plug

☐ F ☐ Dimmer ☐ LED
☐ IP20 ☐ Bi-volt ☐ 50-60Hz ☐ PUSH

Application Floor Lamps

Packaging

- 1 Box
- 0.72 m x 0.72 m x 0.96 m
- Gross weight 6
- Net weight 4.46
- Vol. 0.4976

Lighting effect

General Lighting


Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric Data

Efficiency 58.00 lm/W
Coordinate System CG
Total Flux 444.45 lm
Maximum Value 171.27 cd

Other Applications



All of our products come with a five-year warranty.
Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6, 08850 Gavà, Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com