Circle of Light Soft Plate 900 mm SA.1052.1 - Black

Lighting system, seamless ceiling mounted, for 36 individual LED lighting spots. Set of 12 spots, complete with junction box, power supply and cables, has to be ordered separately. The 1-10V version is dimmable from 10% to 100%.

Lighting system, seamless ceiling mounted, for 36 individual LED lighting spots. Set of 12 spots, complete with junction box, power supply and cables, has to be ordered separately. The 1-10V version is dimmable from 10% to 100%.

Main specifications

IVIAIN Specifications Mountings Environment	Ceiling recessed Indoor		
Optical			
Lighting type Light distribution	Direct Symmetric	90° 90° 60° 60° 30° 110462 cd 30° Luminous flux luminaire 6183 lm	Beam Angle: 12 h(m) E(lx) D(m 1 110462 0.23 2 27616 0.43 3 12274 0.63 4 6904 0.83 5 4418 1.03
Electrical			
Driver Emergency Insulation class	Remote Without II		
Physical			
Color Recessed depth (mm)	Black 150		



Certification / Marking


Note

Weight (kg)


Accent Lighting and General Lighting: 3 units must be ordered (accessories).

28.80





<u>en Alt Alt Alt</u> an





Accent Lighting. Set of 12 spots x 370 Im 3000K CRI 90 08.8572.14C

08.8572.14C1V 08.8572.14C1V Accent Lighting. Set of 12 spots x 370 Im 3000K CRI 90. Dimmable DALI 08.8572.14CDA



General Lighting. Set of 12 Spots x 370 08.8573.14C1V Im 3000K CRI 90 08.8573.14C

08.8573.14C1V

General Lighting. Set of 12 spots x 370 Im 3000K CRI 90. Dimmable DALI 08.8573.14CDA



Accent Lighting. Set of 12 spots x 325 lm 2700K CRI 90 08.8662.14C

08.8662.14C1V 08.8662.14C1V Accent Lighting. Set of 12 spots x 325 Im 2700K CRI 90. Dimmable DALI 08.8662.14CDA

General Lighting. Set of 12 spots x 325 Im 2700K CRI 90 08.8663.14C

08.8663.14C1V 08.8663.14C1V General Lighting. Set of 12 spots x 325 Im 2700K CRI 90. Dimmable DALI 08.8663.14CDA